

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.07.2023

Version number 1.3 (replaces version 1.2)

Revision: 27.07.2023

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** KREUL Gold Bronze 50 ml
- **Article number:** 99462
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Paint
For artists and hobby user.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
C. KREUL GmbH & Co. KG
Carl-Kreul-Straße 2
D-91352 HALLERNDORF
GERMANY
Phone: + 49 (0) 9545/925 - 0
Fax: + 49 (0) 9545/925 - 511
info@c-kreul.de
- **Further information obtainable from:**
Product Safety Department:
Treiber, b.treiber@c-kreul.de
- **1.4 Emergency telephone number:** + 44 (0) 171 635 91 91

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02



GHS07



GHS09

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Solvent naphtha (petroleum), light arom.
- **Hazard statements**
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2023

Version number 1.3 (replaces version 1.2)

Revision: 27.07.2023

(Contd. of page 1)

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P243 Take action to prevent static discharges.
- P260 Do not breathe mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection / face protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with regional regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	25-<50%
CAS: 7440-50-8 EINECS: 231-159-6 Reg.nr.: 01-2119480154-42-XXX	copper ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Eye Irrit. 2, H319	10-<20%
CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37-XXXX	zinc powder -zinc dust (stabilized) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

4.1 Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Wash with water and acidic soap.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Remove contact lenses.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
If symptoms persist consult doctor.
Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2023

Version number 1.3 (replaces version 1.2)

Revision: 27.07.2023

(Contd. of page 2)

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:**
Do not store together with oxidising and acidic materials as well as heavy-metal compounds.
Store away from flammable substances.
Do not store together with alkalis (caustic solutions).
- **Further information about storage conditions:**
Keep container tightly sealed.
Protect from heat and direct sunlight.
- **Storage class:** 3
- **7.3 Specific end use(s)** See chapter 1.2.

8 Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

7440-50-8 copper

WEL	Short-term value: 2** mg/m ³ Long-term value: 0.2* 1** mg/m ³ *fume **dusts and mists (as Cu)
-----	---

· DNELs

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	long-term exposure-systemic effects	11 mg/kg (general population)
Dermal	long-term exposure-systemic effects	11 mg/kg bw/d (general population) 25 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	32 mg/m ³ (general population) 150 mg/m ³ (worker)

7440-50-8 copper

Oral	long-term exposure-systemic effects	0.16 mg/kg (general population)
Dermal	long-term exposure-systemic effects	137 mg/kg bw/d (general population) 137 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	18.2 mg/m ³ (general population) 18.2 mg/m ³ (worker)

7440-66-6 zinc powder -zinc dust (stabilized)

Oral	long-term exposure-systemic effects	0.83 mg/kg (general population)
Dermal	long-term exposure-systemic effects	83 mg/kg bw/d (general population) 83 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	2.5 mg/m ³ (general population) 5 mg/m ³ (worker)

· PNECs

7440-50-8 copper

freshwater	0.0078 mg/l
------------	-------------

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2023

Version number 1.3 (replaces version 1.2)

Revision: 27.07.2023

(Contd. of page 3)

marine water	0.0052 mg/l
sewage treatment plant (STP)	0.23 mg/l
freshwater sediment	87 mg/kg
marine sediment	676 mg/kg
soil	65.5 mg/kg
7440-66-6 zinc powder -zinc dust (stabilized)	
freshwater	0.0206 mg/l
marine water	0.0061 mg/l
sewage treatment plant (STP)	0.0052 mg/l
freshwater sediment	87 mg/kg
marine sediment	56.5 mg/kg
soil	35.6 mg/kg

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.3 mm

Value for the permeation: Level ≤ 8 h

· **As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level ≤ 0.5 h

· **Eye/face protection**



Tightly sealed goggles

9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

162 °C

· **Flammability**

Flammable.

· **Lower and upper explosion limit**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Flash point:**

45 °C

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2023

Version number 1.3 (replaces version 1.2)

Revision: 27.07.2023

(Contd. of page 4)

· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity at 40 °C	>21.5 mm ² /s (DIN 53211/4)
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.1 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	34.50 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases	
· in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4h	>10.2 mg/m ³ (rat)

7440-50-8 copper

Oral	LD50	500 mg/kg (ATE)
------	------	-----------------

7440-66-6 zinc powder -zinc dust (stabilized)

Oral	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4h	5.41 mg/l (rat)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2023

Version number 1.3 (replaces version 1.2)

Revision: 27.07.2023

(Contd. of page 5)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties
--

None of the ingredients is listed.

12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

64742-95-6 Solvent naphtha (petroleum), light arom.
--

LC50/96h	>1,000 mg/l (oncorhynchus mykiss)
----------	-----------------------------------

EC50/48h	>1,000 mg/l (daphnia magna)
----------	-----------------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **14.1 UN number or ID number**

· ADR, IMDG, IATA	UN1263
--------------------------	--------

- **14.2 UN proper shipping name**

· ADR	1263 PAINT, ENVIRONMENTALLY HAZARDOUS
· IMDG	PAINT (TURPENTINE, copper), MARINE POLLUTANT
· IATA	PAINT

- **14.3 Transport hazard class(es)**

- **ADR, IMDG**



· Class	3 Flammable liquids.
· Label	3

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2023

Version number 1.3 (replaces version 1.2)

Revision: 27.07.2023

(Contd. of page 6)

· IATA



· **Class** 3 Flammable liquids.
 · **Label** 3

· **14.4 Packing group**
 · **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:** Product contains environmentally hazardous substances: Solvent naphtha (petroleum), light arom.
 · **Marine pollutant:** Symbol (fish and tree)
 · **Special marking (ADR):** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Flammable liquids.
 · **Hazard identification number (Kemler code):** 30
 · **EMS Number:** F-E,S-E
 · **Stowage Category** A

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**
 · **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml
 · **Transport category** 3
 · **Tunnel restriction code** D/E

· **IMDG**
 · **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
E1 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product Safety Department

· **Contact:** B. Treiber, b.treiber@c-kreul.de

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2023

Version number 1.3 (replaces version 1.2)

Revision: 27.07.2023

(Contd. of page 7)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

GB