

Printing date 01.12.2022 Version number 1.1 Revision: 01.12.2022

## 1 Identification

- · Product identifier
- · Trade name: KREUL Silver Bronze 50 ml
- · Article number: 99461
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Paint

For artists and hobby user.

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

GERMANY

Phone: +49 (0) 9545/925 - 0

Fax: + 49 (0) 9545/925 - 511

info@c-kreul.de

Importer

Zart Art Pty Ltd

48 Overseas Drive

Noble Park North 3174

VIC

Australia

Phone: 61 3 9890 1867 / Fax: 61 3 9898 6527

- Further information obtainable from: Phone: 61 3 9890 1867 / Fax: 61 3 9898 6527
- · Emergency telephone number: Poison Centre, Phone: 13 11 26

# 2 Hazard(s) Identification

· Classification of the substance or mixture



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







GHS02

GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

· Hazard statements

H226 Flammable liquid and vapour.

(Contd. on page 2)

Printing date 01.12.2022 Version number 1.1 Revision: 01.12.2022

(Contd. of page 1)

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/

shower

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## 3 Composition and Information on Ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	25-<50%
EC number: 918-668-5	<ul> <li>Flam. Liq. 3, H226;</li> <li>♠ Asp. Tox. 1, H304;</li> <li>♠ Aquatic Chronic 2, H411;</li> <li>♦ STOT SE 3, H335-H336</li> </ul>	
CAS: 7429-90-5	aluminium powder (stabilised)	10-<20%
EINECS: 231-072-3 Index number: 013-002-00-1	Flam. Sol. 1, H228	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **4 First Aid Measures**

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

If symptoms persist consult doctor.

Rinse out mouth and then drink plenty of water.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **5 Fire Fighting Measures**

- · Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## **6 Accidental Release Measures**

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)

Version number 1.1 Printing date 01.12.2022 Revision: 01.12.2022

(Contd. of page 2)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# 7 Handling and Storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility:

Store away from flammable substances.

Do not store together with oxidising and acidic materials as well as heavy-metal compounds.

Do not store together with alkalis (caustic solutions).

Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

- · Storage class: 3
- · Specific end use(s) See chapter 1.2.

### 8 Exposure controls and personal protection

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs					
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.				
Oral	long-term exposure-systemic effects	11 mg/kg (general population)			
Dermal	long-term exposure-systemic effects	11 mg/kg bw/d (general population)			
		25 mg/kg bw/d (worker)			
Inhalative	long-term exposure-systemic effects	32 mg/m³ (general population)			
		150 mg/m³ (worker)			

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.3$  mm

Value for the permeation: Level  $\leq 8 \text{ h}$ 

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level  $\leq 0.5 \text{ h}$ 

Eye protection:



Tightly sealed goggles

Printing date 01.12.2022 Version number 1.1 Revision: 01.12.2022

(Contd. of page 3)

9 Physical and Chemical Propert	ies
· Information on basic physical and che · General Information · Appearance:	mical properties
Form:	Fluid
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. 2: 162 °C
· Flash point:	45 °C
· Flammability (solid, gas):	Flammable.
· Decomposition temperature:	Not determined.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.99 g/cm <sup>3</sup>
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C:	>21.5 mm²/s (DIN 53211/4)
· Other information	No further relevant information available.

# 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 v	· LD/LC50 values relevant for classification:			
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	>6,800 mg/kg (rat)		
Dermal	LD50	>3,400 mg/kg (rab)		
		>10.2 mg/m³ (rat)		
7429-90-5	7429-90-5 aluminium powder (stabilised)			
Oral	LD50	>2,000 mg/kg (rat)		
Inhalative	LC50/4h	888 mg/m³ (rat)		

- Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

- AL

Version number 1.1 Printing date 01.12.2022 Revision: 01.12.2022

(Contd. of page 4)

## 12 Ecological Information

- · Toxicity
- Aquatic toxicity:

64742-95-6 Solvent naphtha (petroleum), light arom.

LC50/96h >1,000 mg/l (oncorhynchus mykiss)

EC50/48h >1,000 mg/l (daphnia magna)

- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

UN-Number ADG, IMDG, IATA	UN1263
UN proper shipping name ADG IMDG IATA	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (TURPENTINE), MARINE POLLUTANT PAINT
Transport hazard class(es)	
ADG, IMDG	
<b>1 1 1 1 1 1 1 1 1 1</b>	
Class Label	3 Flammable liquids. 3
IATA	
Class	3 Flammable liquids.
Label	3
Packing group ADG, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substanc Solvent naphtha (petroleum), light arom.
Marine pollutant:	Yes (DOT) Symbol (fish and tree)
Special marking (ADG):	Symbol (fish and tree)
Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Flammable liquids. 30 F-E,S-E

Version number 1.1 Revision: 01.12.2022 Printing date 01.12.2022

	(Contd. of page
· Stowage Category	A
· Transport in bulk according to Annex II of Marpol and th IBC Code	ne Not applicable.
· Transport/Additional information:	
· ADG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Australian Inventory of Industrial Chemicals

We confirm that they we are have checked the AICS under here https://www.industrialchemicals.gov.au/search-inventory and we can confirm that each ingredient is either listed on the AICS and within the allowable limit or meets restrictions on said ingredient.

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed

**Australia: Priority Existing Chemicals** 

None of the ingredients is listed.

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







GHS09

GHS02

GHS07 Signal word Warning

- · Hazard-determining components of labelling:
- Solvent naphtha (petroleum), light arom.
- Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P241 Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Version number 1.1 Printing date 01.12.2022 Revision: 01.12.2022

(Contd. of page 6)

#### Relevant phrases

H226 Flammable liquid and vapour.

H228 Flammable solid.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Contact: Phone: 61 3 9890 1867 / Fax: 61 3 9898 6527

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

PB1: Persistent, Bloaccumulative and 1 oxic
VPVB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Sol. 1: Flammable solids – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2