

Printing date 16.11.2022 Version number 1.3 Revision: 16.11.2022

1 Identification

- · Product identifier
- · Trade name: KREUL Acrylic Matt Varnish synthetic resin-based 50 ml, 250 ml
- · Article number: 79409, 79410
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Lacquer

For artists and hobby user.

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

C. KREUL GmbH & Co. KG Carl-Kreul-Straße 2 D-91352 HALLERNDORF

GERMANY

Phone: + 49 (0) 9545/925 - 0 Fax: + 49 (0) 9545/925 - 511

info@c-kreul.de

Importer Zart Art Pty Ltd 48 Overseas Drive Noble Park North 3174 VIC

Australia

Phone: 61 3 9890 1867 / Fax: 61 3 9898 6527

- · Further information obtainable from: Phone: 61 3 9890 1867 / Fax: 61 3 9898 6527
- · Emergency telephone number: Poison Centre, Phone: 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02

.

- · Signal word Warning
- · Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

Printing date 16.11.2022 Version number 1.3 Revision: 16.11.2022

(Contd. of page 1)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary measures against static discharges.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
ĺ		Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics	25-<50%
	EC number: 919-857-5	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
ſ	CAS: 64742-95-6	Hydrocarbons, C9, aromatics	10-<20%
		♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

Seek immediate medical advice.

· After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Administer medicinal carbon.

A person vomiting while laying on their back should be turned onto their side.

Seek immediate medical advice.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Mount respiratory protective device.

Environmental precautions:

Keep contaminated washing water and dispose of appropriately.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Printing date 16.11.2022 Version number 1.3 Revision: 16.11.2022

(Contd. of page 2)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- Precautions for safe handling

Take note of emission threshold.

Prevent formation of aerosols.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

No special requirements.

Store in a cool location.

· Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

· Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace

DNELs			
64742-48-	64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics		
Oral	long-term exposure-systemic effects	300 mg/kg (general population)	
Dermal	long-term exposure-systemic effects	300 mg/kg bw/d (general population)	
		300 mg/kg bw/d (worker)	
Inhalative	long-term exposure-systemic effects	900 mg/m³ (general population)	
		1,500 mg/m³ (worker)	
64742-95-	64742-95-6 Hydrocarbons, C9, aromatics		
Oral	long-term exposure-systemic effects	11 mg/kg (general population)	
Dermal	long-term exposure-systemic effects	11 mg/kg bw/d (general population)	
		25 mg/kg bw/d (worker)	
Inhalative	long-term exposure-systemic effects	32 mg/m³ (general population)	
		150 mg/m³ (worker)	

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level \leq 8 h

(Contd. on page 4)

Version number 1.3 Printing date 16.11.2022 Revision: 16.11.2022

(Contd. of page 3)

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.12 \text{ mm}$

Value for the permeation: Level \leq 2-4 h

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

9 Physical and Chemical Properties

Information on basic physical and of	chemical	properties
--------------------------------------	----------	------------

- **General Information**
- Appearance:

pH-value:

Form: Fluid Odour: Characteristic · Odour threshold: Not determined.

Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

· Flash point: >23 °C

· Flammability (solid, gas): Not applicable. · Ignition temperature: <237 °C

Decomposition temperature: Not determined.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are

Not determined.

Not determined.

· Explosion limits: Lower:

0.8 Vol % Upper: 7 Vol % · Vapour pressure at 20 °C: 3 hPa

Density at 20 °C: 0.87 g/cm³ Relative density Not determined. Vapour density Not determined. · Evaporation rate Not determined.

Solubility in / Miscibility with

Not miscible or difficult to mix. water:

· Partition coefficient: n-octanol/water: Viscosity:

Dynamic: Not determined. Kinematic at 40 °C: >20.5 mm²/s

· Solvent content:

Organic solvents: 64 % Solids content:

Other information No further relevant information available.

10 Stability and Reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: Keep away from oxidizing agents, strong alkaline and acidic materials.
- · Hazardous decomposition products:

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Printing date 16.11.2022 Version number 1.3 Revision: 16.11.2022

(Contd. of page 4)

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity

	· LD/LC50 values relevant for classification:	
I	ATE (Acute Toxicity Estimates)	
I	Inhalative LC50/4h >9,902–19,804 mg/m³ (rat)	

Į	Innalative LC-50/4n >9,902–19,804 mg/m³ (rat)			
ſ	64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics			
ľ	Oral LD50 >5,000 mg/kg (rat)			
	Dermal	LD50	>5,000 mg/kg (rab)	
	Inhalative	LC50/4h	>4,951 mg/m³ (rat)	
ſ	64742-95-6 Hydrocarbons, C9, aromatics			
ľ	Oral	LD50	>6,800 mg/kg (rat)	
	Dermal	LD50	>3,400 mg/kg (rab)	
	Inhalative	LC50/4h	>10.2 mg/m³ (rat)	

12 Ecological Information

· Toxicity

· Aquatic toxicity:		
64742-95-6	6 Hydrocarbons, C9, aromatics	
LC50/96h	>1,000 mg/l (oncorhynchus mykiss)	
EC50/48h	>1,000 mg/l (daphnia magna)	

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- General notes:

Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · ADG, IMDG, IATA	UN1263
· UN proper shipping name · ADG	1263 PAINT
· IMDG, IATA	PAINT

- · Transport hazard class(es)
- · ADG, IMDG, IATA



· Class	3 Flammable liquids.
· Labol	2

· Packing group

· ADG, IMDG, IATA

(Contd. on page 6)

Printing date 16.11.2022 Version number 1.3 Revision: 16.11.2022

	(Contd. of pag
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
Transport in bulk according to Annex II of Marpol	and the
IBC Code	Not applicable.
Transport/Additional information:	
· ADG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Australian Inventory of Industrial Chemicals

We confirm that they we are have checked the AICS under here https://www.industrialchemicals.gov.au/search-inventory and we can confirm that each ingredient is either listed on the AICS and within the allowable limit or meets restrictions on said ingredient.

All ingredients are listed.

- · Standard for the Uniform Scheduling of Medicines and Poisons
- None of the ingredients is listed.
- · Australia: Priority Existing Chemicals

None of the ingredients is listed.

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02

- · Signal word Warning
- · Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

- Hazard statements
- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Version number 1.3 Printing date 16.11.2022 Revision: 16.11.2022

(Contd. of page 6)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Contact: Phone: 61 3 9890 1867 / Fax: 61 3 9898 6527

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

VPVB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3