

# Safety Data Sheet according to WHS Regulations

Printing date 17.11.2022

Version number 1.3

Revision: 17.11.2022

1 Idontificatio	
1 Identificatio	
· Product identit	
	REUL Acrylic Satin Varnish synthetic resin-based 50 ml, 250 ml
No further relev • Application of Lacquer	ified uses of the substance or mixture and uses advised against ant information available. the substance / the mixture
For artists and I	
<ul> <li>Details of the s</li> <li>Manufacturer/S</li> <li>C. KREUL Gmb Carl-Kreul-Stral</li> <li>D-91352 HALLE</li> <li>GERMANY</li> <li>Phone: + 49 (0)</li> <li>Fax: + 49 (0) 95</li> <li>info@c-kreul.de</li> </ul>	DH & Co. KG 3e 2 ERNDORF 9545/925 - 0 545/925 - 511
Importer	
Zart Art Pty Ltd 48 Overseas Dr Noble Park Nor VIC Australia	th 3174
Phone: 61 3 98	90 1867 / Fax: 61 3 9898 6527
	ation obtainable from: Phone: 61 3 9890 1867 / Fax: 61 3 9898 6527 ephone number: Poison Centre, Phone: 13 11 26
Classification	of the substance or mixture
	of the substance or mixture S02 flame
GH	S02 flame H226 Flammable liquid and vapour.
Flam. Liq. 3	S02 flame H226 Flammable liquid and vapour.
Flam. Liq. 3 Flam. Liq. 3 GH3 STOT SE 3	S02 flame H226 Flammable liquid and vapour. S07
Flam. Liq. 3 Flam. Liq. 3 GH3 STOT SE 3 Aquatic Chronic	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. 3 H412 Harmful to aquatic life with long lasting effects. <b>s</b> nents The product is classified and labelled according to the Globally Harmonised System (GHS).
Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 GH: STOT SE 3 Aquatic Chronic Chabel elements GHS label elem Hazard pictogr	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. 3 H412 Harmful to aquatic life with long lasting effects. sneets The product is classified and labelled according to the Globally Harmonised System (GHS). rams
Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 GHS GHS 12 GHS 12 G	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. 3 H412 Harmful to aquatic life with long lasting effects. sneets The product is classified and labelled according to the Globally Harmonised System (GHS). rams
Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 GHS STOT SE 3 Aquatic Chronic Chronic GHS label elements GHS label el	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. 3 H412 Harmful to aquatic life with long lasting effects. Senents The product is classified and labelled according to the Globally Harmonised System (GHS). rams HS07 Harming
Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 GHS GHS GHS GHS GHS GHS GHS GHS	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. 2 3 H412 Harmful to aquatic life with long lasting effects. senents The product is classified and labelled according to the Globally Harmonised System (GHS). rams HS07 'arming tining components of labelling: C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ents
Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 GHS STOT SE 3 Aquatic Chronic Label elements GHS label elem Hazard pictogr GHS02 GHS02 G Signal word W Hazard-determ Hydrocarbons, 0 Hazard statem H226 Flammab	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. : 3 H412 Harmful to aquatic life with long lasting effects. senents The product is classified and labelled according to the Globally Harmonised System (GHS). rams Floor HS07 HS07 Harming ining components of labelling: C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ents le liquid and vapour.
Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 GHS STOT SE 3 Aquatic Chronic Label elements GHS label elem Hazard pictogr GHS02	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. 3 H412 Harmful to aquatic life with long lasting effects. annets The product is classified and labelled according to the Globally Harmonised System (GHS). Tarms HS07 HS07 tarming tining components of labelling: C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ents le liquid and vapour. e drowsiness or dizziness. o aquatic life with long lasting effects.
Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 GHS STOT SE 3 Aquatic Chronic Label elements GHS label elem Hazard pictogr GHS02	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. 3 H412 Harmful to aquatic life with long lasting effects. senents The product is classified and labelled according to the Globally Harmonised System (GHS). rams Floor HS07 HS07 Arming ining components of labelling: C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ents le liquid and vapour. e drowsiness or dizziness. o aquatic life with long lasting effects. statements
Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 Flam. Liq. 3 GHS STOT SE 3 Aquatic Chronic Hazard pictogr GHS label elem Hazard pictogr GHS02	S02 flame H226 Flammable liquid and vapour. S07 H336 May cause drowsiness or dizziness. 3 H412 Harmful to aquatic life with long lasting effects. annets The product is classified and labelled according to the Globally Harmonised System (GHS). Tarms HS07 HS07 tarming tining components of labelling: C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ents le liquid and vapour. e drowsiness or dizziness. o aquatic life with long lasting effects.

## Safety Data Sheet according to WHS Regulations

Printing date 17.11.2022

Version number 1.3

Revision: 17.11.2022

P210	(Contd. of page 1) Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
. =	353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Other hazards	
other sources measures again	form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary inst static discharges. T and vPvB assessment
• PBT: Not appli	

**vPvB:** Not applicable.

### **3 Composition and Information on Ingredients**

· Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

Dangerous components.		
CAS: 64742-48-9 Hy	ydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics	25-<75%
EC number: 919-857-5 🐼	> Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; 🚸 STOT SE 3, H336	
	,	10-<20%
	Flam. Liq. 3, H226; 🗞 Asp. Tox. 1, H304; 🚯 Aquatic Chronic 2, H411; 🚸 STOT SE H335-H336	
A statistic section from a first sector of the sector		

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **4 First Aid Measures**

#### Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air; consult doctor in case of complaints.
- In case of unconsciousness place patient stably in side position for transportation.
- Seek immediate medical advice.
- · After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.
- · After eye contact:
- Remove contact lenses
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing:
- Rinse out mouth and then drink plenty of water.
- Administer medicinal carbon.
- A person vomiting while laying on their back should be turned onto their side.
- Seek immediate medical advice.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- If swallowed or in case of vomiting, danger of entering the lungs.

#### **5 Fire Fighting Measures**

- Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## **6 Accidental Release Measures**


- Personal precautions, protective equipment and emergency procedures
   Ensure adequate ventilation
- Ensure adequate ventilation
- Use respiratory protective device against the effects of fumes/dust/aerosol.
- Keep away from ignition sources.
- Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
- Keep contaminated washing water and dispose of appropriately.
- Inform respective authorities in case of seepage into water course or sewage system.

## Safety Data Sheet according to WHS Regulations

Printing date 17.11.2022

Version number 1.3

Revision: 17.11.2022



## Safety Data Sheet according to WHS Regulations

Printing date 17.11.2022

Version number 1.3

Revision: 17.11.2022

<ul> <li>As protection from splashes gloves manual Nitrile rubber, NBR</li> <li>Recommended thickness of the material: Value for the permeation: Level ≤ 2-4 h</li> <li>Eye protection:</li> <li>Tightly sealed goggles</li> <li>Body protection: Protective work clothing</li> </ul>	
9 Physical and Chemical Properti	es
<ul> <li>Information on basic physical and chere</li> <li>General Information</li> <li>Appearance:</li> <li>Form:</li> <li>Odour:</li> <li>Odour threshold:</li> </ul>	Fluid Characteristic Not determined.
· pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : Undetermined.
· Flash point:	>23 °C
· Flammability (solid, gas):	Flammable.
· Ignition temperature:	<237 °C
· Decomposition temperature:	Not determined.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	0.8 Vol % 7 Vol %
· Vapour pressure at 20 °C:	3.1 hPa
Density at 20 °C: Relative density Vapour density Evaporation rate	0.875 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
<ul> <li>Viscosity: Dynamic: Kinematic at 40 °C:</li> </ul>	Not determined. >20.5 mm²/s
<ul> <li>Solvent content: Organic solvents:</li> </ul>	66 %
Solids content:	34 %
· Other information	No further relevant information available.

## 10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· Incompatible materials: Keep away from oxidizing agents, strong alkaline and acidic materials.

Hazardous decomposition products:

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

(Contd. on page 5)

AU

Printing date 17.11.2022

Version number 1.3

Revision: 17.11.2022

(Contd. of page 4)

1	ΙΟΧΙ	colog	ical in	itormat	lon

٠l	nformation	on	toxico	logical	effects
----	------------	----	--------	---------	---------

· Acute toxicity						
· LD/LC50 values relevant for classification:						
64742-48-	9 Hydroc	arbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics				
Oral	LD50	>5,000 mg/kg (rat)				
Dermal	LD50	>5,000 mg/kg (rab)				
Inhalative	LC50/4h	>4,951 mg/m³ (rat)				
64742-95-	6 Hydroc	arbons, C9, aromatics				
Oral	LD50	>6,800 mg/kg (rat)				
Dermal	LD50	>3,400 mg/kg (rab)				
Inhalative	LC50/4h	>10.2 mg/m³ (rat)				
· Primary ir						
· Skin corrosion/irritation No irritant effect.						

· Serious eye damage/irritation No irritating effect.

· Respiratory or skin sensitisation No sensitising effects known.

## **12 Ecological Information**

Toxicity

#### Aquatic toxicity:

64742-95-6 Hydrocarbons, C9, aromatics

LC50/96h >1,000 mg/l (oncorhynchus mykiss)

- EC50/48h >1,000 mg/l (daphnia magna)
- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- General notes:
- Harmful to aquatic organisms
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

## **14 Transport information**

UN-Number ADG, IMDG, IATA	UN1263	
UN proper shipping name ADG IMDG, IATA	1263 PAINT PAINT	
Transport hazard class(es)		
ADG, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	

## Safety Data Sheet according to WHS Regulations

Printing date 17.11.2022

Version number 1.3

	(Contd. of page
Packing group	
ADG, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
Transport in bulk according to Annex II of Marpol a	and the
IBC Code	Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
· Tunnel restriction code	D/E
IMDG	
· Limited quantities (LQ)	5L
<ul> <li>Excepted quantities (EQ)</li> </ul>	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT. 3. III

## 15 Regulatory information

#### · Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory of Industrial Chemicals

We confirm that they we are have checked the AICS under here https://www.industrialchemicals.gov.au/search-inventory and we can confirm that each ingredient is either listed on the AICS and within the allowable limit or meets restrictions on said ingredient.

All ingredients are listed.

#### · Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

#### · Australia: Priority Existing Chemicals

None of the ingredients is listed.

• **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS). • **Hazard pictograms** 



· Signal word Warning

#### · Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

- Hazard statements
- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 7)

Printing date 17.11.2022

Version number 1.3

Revision: 17.11.2022

## · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 6)

1	6	0	th	er	in	for	ma	tior	ſ

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Relevant phrases H226 Flammable liquid and vapour.

- H304 May be fatal if swallowed and enters airways.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- · Contact:
- Abbreviations and acronyms:
   ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous
   Goods by Road)
   IMDG: International Maritime Code for Dangerous Goods
   MTA International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

- LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids Category 3 STOT SE 3: Specific target organ toxicity (single exposure) Category 3 Asp. Tox. 1: Aspiration hazard Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment long-term aquatic hazard Category 3

٩U