

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.07.2022 Version number 1.0 Revision: 13.07.2022

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: KREUL Varnish glossy 50 ml, 250 ml, 1000 ml
- · Article number: 86150, 86155, 86159
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Painting Medium

For artists and hobby user.

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

DEUTSCHLAND

Tel. + 49 (0)9545 / 925 - 0

Fax + 49 (0)9545 / 925 - 511

E-Mail: info@c-kreul.de

· Further information obtainable from:

Product Safety Department:

Treiber, b.treiber@c-kreul.de

· 1.4 Emergency telephone number: +44 (0)171 635 91 91

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





· Signal word Warning

· Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 2)

Printing date 13.07.2022 Version number 1.0 Revision: 13.07.2022

(Contd. of page 1)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics ♠ Flam. Liq. 3, H226; ♣ Asp. Tox. 1, H304; ♠ STOT SE 3, H336	25-<50%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics ♠ Flam. Liq. 3, H226; ♠ Asp. Tox. 1, H304; ♠ Aquatic Chronic 2, H411; ♠ STOT SE 3, H335-H336	12.5-<20%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water.

After swallowing:

Rinse out mouth and then drink plenty of water.

Inform doctor. Do not give milk or fatty oils.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 3)

Printing date 13.07.2022 Version number 1.0 Revision: 13.07.2022

(Contd. of page 2)

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Protect from heat

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

- Storage class: 3
- 7.3 Specific end use(s) See chapter 1.2.

8 Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELS					
64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics					
Oral	long-term exposure-systemic effects	300 mg/kg (general population)			
Dermal	long-term exposure-systemic effects	300 mg/kg bw/d (general population)			
		300 mg/kg bw/d (worker)			
Inhalative	long-term exposure-systemic effects	900 mg/m³ (general population)			
		1,500 mg/m³ (worker)			
64742-95-	6 Hydrocarbons, C9, aromatics				
Oral	long-term exposure-systemic effects	11 mg/kg (general population)			
Dermal	long-term exposure-systemic effects	11 mg/kg bw/d (general population)			
		25 mg/kg bw/d (worker)			
Inhalative	long-term exposure-systemic effects	32 mg/m³ (general population)			
		150 mg/m³ (worker)			

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.4 \text{ mm}$

Value for the permeation: Level $\leq 8h$

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.12 \ mm$

(Contd. on page 4)


Version number 1.0 Revision: 13.07.2022 Printing date 13.07.2022

Not applicable.

(Contd. of page 3)

Value for the permeation: Level \leq 2-4h

Eye/face protection



9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Colour: According to product specification

· Odour: Characteristic Odour threshold: Not determined. Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling range 155 °C

Flammability

· Lower and upper explosion limit

· Lower: 0.8 Vol % · Upper: 7 Vol % Flash point: >23 °C · Ignition temperature: <237 °C · Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

Kinematic viscosity at 20 °C 25 s (DIN 53211/4) · Dynamic: Not determined.

· Solubility

Not miscible or difficult to mix. water:

· Partition coefficient n-octanol/water (log value) Not determined 2.9 hPa

· Vapour pressure at 20 °C:

Density and/or relative density

Density at 20 °C: 0.9 g/cm³ Relative density Not determined. Vapour density Not determined.

9.2 Other information

Appearance:

· Form: Fluid Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Solvent content: Organic solvents: 58 % · Solids content: 42 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void

Flammable liquids

Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids

Void **Oxidising solids** Void Organic peroxides Void Corrosive to metals Void Desensitised explosives Void

Printing date 13.07.2022 Version number 1.0 Revision: 13.07.2022

(Contd. of page 4)

10 Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:					
64742-48-	64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics					
Oral	LD50	>5,000 mg/kg (rat)				
Dermal	LD50	>5,000 mg/kg (rab)				
		>4,951 mg/m³ (rat)				
64742-95-	64742-95-6 Hydrocarbons, C9, aromatics					
Oral	LD50	>6,800 mg/kg (rat)				
Dermal	LD50	>3,400 mg/kg (rab)				
Inhalative	LC50/4h	>10.2 mg/m³ (rat)				

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

64742-95-6 Hydrocarbons, C9, aromatics

LC50/96h >1,000 mg/l (oncorhynchus mykiss) EC50/48h >1,000 mg/l (daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground

13 Disposal considerations

- · 13.1 Waste treatment methods
- $\cdot \textbf{Recommendation} \ \text{Must not be disposed together with household garbage}. \ Do \ not \ allow \ product \ to \ reach \ sewage \ system.$
- · Uncleaned packaging:
- \cdot Recommendation: Disposal must be made according to official regulations.

(Contd. on page 6)

Printing date 13.07.2022 Version number 1.0 Revision: 13.07.2022

· Recommended cleansing agents: Solvent naphtha

(Contd. of page 5)

Transport information	
<u> </u>	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
· ADR	1263 PAINT
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code): · EMS Number:	30 F-E,S-E
Stowage Category	F-E, <u>S-E</u> A
· 14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
, , , , ,	Maximum net quantity per inner packaging: 30 ml
· Transport category	Maximum net quantity per outer packaging: 1000 ml
· Tunnel restriction code	D/E
· IMDG	
· IMDG · Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
. , , ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- \cdot Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product Safety Department
- · Contact: B. Treiber, b.treiber@c-kreul.de

(Contd. on page 7)

Page 7/7

(Contd. of page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.07.2022 Version number 1.0 Revision: 13.07.2022

ADBreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal concentration, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
VPVB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3