

Printing date 17.11.2022 Version number 1.1 (replaces version 1.0) Revision: 17.11.2022

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: KREUL Wood stain varnish matt 250 ml
- · Article number: 78260
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Lacquer

For artists and hobby user.

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

GERMANY

Phone: +49 (0) 9545/925 - 0

Fax: + 49 (0) 9545/925 - 511

info@c-kreul.de

· Further information obtainable from:

Product Safety Department:

Treiber, b.treiber@c-kreul.de

· 1.4 Emergency telephone number: + 44 (0) 171 635 91 91

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





· Signal word Warning

Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2022 Version number 1.1 (replaces version 1.0) Revision: 17.11.2022

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary measures against static discharges.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--------------------------------|---|----------|
| CAS: 64742-48-9 | Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics | 20-<50% |
| EC number: 919-857-5 | ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336 | |
| Reg.nr.: 01-2119463258-33-XXXX | | |
| CAS: 64742-95-6 | Hydrocarbons, C9, aromatics | 2.5-<20% |
| EC number: 918-668-5 | ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; | |
| Reg.nr.: 01-2119455851-35-XXXX | | |

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

Seek immediate medical advice.

· After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Administer medicinal carbon.

A person vomiting while laying on their back should be turned onto their side.

Seek immediate medical advice.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Mount respiratory protective device.

· 6.2 Environmental precautions:

Keep contaminated washing water and dispose of appropriately.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

(Contd. on page 3)

Printing date 17.11.2022 Version number 1.1 (replaces version 1.0) Revision: 17.11.2022

(Contd. of page 2)

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Take note of emission threshold.

Prevent formation of aerosols.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles:

No special requirements.

Store in a cool location.

· Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

| DNELs | DNELs | | | | |
|--|--|-------------------------------------|--|--|--|
| 64742-48- | 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics | | | | |
| Oral | long-term exposure-systemic effects | 300 mg/kg (general population) | | | |
| Dermal | long-term exposure-systemic effects | 300 mg/kg bw/d (general population) | | | |
| | | 300 mg/kg bw/d (worker) | | | |
| Inhalative | long-term exposure-systemic effects | 900 mg/m³ (general population) | | | |
| | | 1,500 mg/m³ (worker) | | | |
| 64742-95-6 Hydrocarbons, C9, aromatics | | | | | |
| Oral | long-term exposure-systemic effects | 11 mg/kg (general population) | | | |
| Dermal | long-term exposure-systemic effects | 11 mg/kg bw/d (general population) | | | |
| | | 25 mg/kg bw/d (worker) | | | |
| Inhalative | long-term exposure-systemic effects | 32 mg/m³ (general population) | | | |
| | | 150 mg/m³ (worker) | | | |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Use suitable respiratory protective device when high concentrations are present.
- Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4

(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.1 (replaces version 1.0) Printing date 17.11.2022 Revision: 17.11.2022

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level \leq 8 h

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.12 mm

Value for the permeation: Level \leq 2-4 h

Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Colour: According to product specification

Characteristic Odour: · Odour threshold: Not determined. Melting point/freezing point: Undetermined · Boiling point or initial boiling point and boiling range Undetermined Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 0.8 Vol % · Upper: 7 Vol % >23 °C Flash point: Ignition temperature: <237 °C Decomposition temperature: Not determined. Not determined. pН

Viscosity:

· Kinematic viscosity at 40 °C >20.5 mm²/s Dynamic: Not determined.

· Solubility water:

Not miscible or difficult to mix. Partition coefficient n-octanol/water (log value) Not determined.

3 hPa

· Vapour pressure at 20 °C:

· Density and/or relative density

Density at 20 °C: 0.88 g/cm³ Relative density Not determined. Vapour density Not determined.

9.2 Other information

Appearance:

Fluid · Form: · Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible. · Solvent content:

· Organic solvents: 64 % · VOC (EC) 64 % · Solids content: 35.9 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

 Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void

· Flammable liquids

Flammable liquid and vapour. Flammable solids Void · Self-reactive substances and mixtures Void Pyrophoric liquids Void

Pyrophoric solids Void

Printing date 17.11.2022 Version number 1.1 (replaces version 1.0) Revision: 17.11.2022

(Contd. of page 4)

| · Self-heating substances and mixtures | Void | |
|--|-----------|--|
| Substances and mixtures, which emit flamma | ble gases | |
| in contact with water | Void | |
| · Oxidising liquids | Void | |
| Oxidising solids | Void | |
| · Organic peroxides | Void | |
| Corrosive to metals | Void | |
| Desensitised explosives | Void | |
| | | |

10 Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Keep away from oxidizing agents, strong alkaline and acidic materials.
- · 10.6 Hazardous decomposition products:

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

11 Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 v | · LD/LC50 values relevant for classification: | | | |
|-------------|--|--------------------|--|--|
| 64742-48- | 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics | | | |
| Oral | LD50 | >5,000 mg/kg (rat) | | |
| Dermal | LD50 | >5,000 mg/kg (rab) | | |
| Inhalative | LC50/4h | >4,951 mg/m³ (rat) | | |
| 64742-95- | 64742-95-6 Hydrocarbons, C9, aromatics | | | |
| Oral | LD50 | >6,800 mg/kg (rat) | | |
| Dermal | LD50 | >3,400 mg/kg (rab) | | |
| Inhalative | LC50/4h | >10.2 mg/m³ (rat) | | |

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

· 12.1 Toxicity

| _ | | | |
|---|--|-----------------------------------|--|
| | · Aquatic toxicity: | | |
| | 64742-95-6 Hydrocarbons, C9, aromatics | | |
| ſ | LC50/96h | >1,000 mg/l (oncorhynchus mykiss) | |
| | EC50/48h | >1,000 mg/l (daphnia magna) | |

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

(Contd. on page 6)

Printing date 17.11.2022 Version number 1.1 (replaces version 1.0) Revision: 17.11.2022

Harmful to aquatic organisms

(Contd. of page 5)

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| 4 Transport information | |
|---|---|
| · 14.1 UN number or ID number · ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name · ADR · IMDG, IATA | 1263 PAINT PAINT |
| · 14.3 Transport hazard class(es) | TAINT |
| · ADR, IMDG, IATA | |
| 3 | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · 14.4 Packing group · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category | Warning: Flammable liquids. 30 F-E, <u>S-E</u> A |
| · 14.7 Maritime transport in bulk according to IM instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code | 5L 3 D/E |
| · IMDG · Limited quantities (LQ) | 5L |
| UN "Model Regulation": | UN 1263 PAINT, 3, III |

15 Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- \cdot Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product Safety Department

(Contd. on page 7)

Page 7/7

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.1 (replaces version 1.0) Printing date 17.11.2022 Revision: 17.11.2022

(Contd. of page 6)

· Contact: B. Treiber, b.treiber@c-kreul.de

· Abbreviations and acronyms:

ADDR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Materials Social (Missian of the American Chemical Social)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
**Para compared to the provious version altered

* Data compared to the previous version altered.