

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.0 Revision: 17.11.2020

1 Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Printing date 17.11.2020

- · Trade name: KREUL Silver Bronze 50 ml
- · Article number: 99461
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint

For artists and hobby user.

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

DEUTSCHLAND

Tel. + 49 (0)9545 / 925 - 0

Fax + 49 (0)9545 / 925 - 511

E-Mail: info@c-kreul.de

Further information obtainable from:

Product Safety Department:

Treiber, b.treiber@c-kreul.de

· 1.4 Emergency telephone number: +44 (0)171 635 91 91

2 Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02

GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.11.2020 Version number 1.0 Revision: 17.11.2020

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges. P261 Avoid breathing mist/vapours/spray. Use only outdoors or in a well-ventilated area. P271

Wear protective gloves/protective clothing/eye protection/face protection. P280 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell. P312 P337+P313 If eye irritation persists: Get medical advice/attention. P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms







GHS02

GHS07

Signal word Warning

Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

Hazard statements

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	25-<50%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45-XXXX	aluminium powder (stabilised) Tilde Flam. Sol. 1, H228	10-<20%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- **General information:** Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Generally the product does not irritate the skin.

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

If symptoms persist consult doctor.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2020 Version number 1.0 Revision: 17.11.2020

(Contd. of page 2)

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility:

Store away from flammable substances.

Do not store together with oxidising and acidic materials as well as heavy-metal compounds.

Do not store together with alkalis (caustic solutions).

Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

7.3 Specific end use(s) See chapter 1.2.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs	· DNELs			
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	long-term exposure-systemic effects	11 mg/kg (general population)		
Dermal	long-term exposure-systemic effects	11 mg/kg bw/d (general population)		
		25 mg/kg bw/d (worker)		
Inhalative	long-term exposure-systemic effects	32 mg/m³ (general population)		
		150 mg/m³ (worker)		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- $\cdot \ \textbf{General protective and hygienic measures:} \ \textbf{Wash hands before breaks and at the end of work.}$

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.0 Printing date 17.11.2020 Revision: 17.11.2020

(Contd. of page 3)

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.3 mm

Value for the permeation: Level \leq 8 h

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber NBR

Recommended thickness of the material: \geq 0.4 mm

Value for the permeation: Level $\leq 0.5 \text{ h}$

Eye protection:



Tightly sealed goggles

g Phi	/eical an	d chamic	al properties

• 9.1	Information	on basic	physical	and	chemical	properties

General Information

Appearance:

Form: Fluid

Colour: According to product specification

Odour: Characteristic Odour threshold: Not determined. Not determined. pH-value:

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 162 °C · Flash point:

· Flammability (solid, gas): Not applicable.

· Decomposition temperature: Not determined.

Product is not explosive. However, formation of explosive air/vapour mixtures are · Explosive properties:

Product is not selfigniting.

possible.

Not determined.

45 °C

· Explosion limits:

Evaporation rate

· Auto-ignition temperature:

Lower: Not determined. Upper: Not determined.

· Vapour pressure: Not determined.

· Density at 20 °C: 0.99 g/cm³ Relative density Not determined. Vapour density Not determined

· Solubility in / Miscibility with

Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic: Not determined.

Kinematic at 40 °C: >21.5 mm²/s (DIN 53211/4)

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2020 Version number 1.0 Revision: 17.11.2020

(Contd. of page 4)

· Solvent content:

Organic solvents: 25–<50 %

• 9.2 Other information No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· 11.1 Information on toxicological effects

· LD/LC50 values relevant for classification:

· Acute toxicity Based on available data, the classification criteria are not met.

ATE (Acu	ATE (Acute Toxicity Estimates)		
Inhalative	LC50/4h	>20.4–40.8 mg/m³ (rat)	
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)	
Dermal	LD50	>3,400 mg/kg (rab)	
Inhalative	LC50/4h	>10.2 mg/m³ (rat)	
7429-90-5	7429-90-5 aluminium powder (stabilised)		
Oral	LD50	>2,000 mg/kg (rat)	
Inhalative	LC50/4h	888 mg/m³ (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause respiratory irritation. May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

64742-95-6 Solvent naphtha (petroleum), light arom.

LC50/96h >1,000 mg/l (oncorhynchus mykiss)

EC50/48h >1,000 mg/l (daphnia magna)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2020 Version number 1.0 Revision: 17.11.2020

(Contd. of page 5)

13 Disposal considerations

- · 13.1 Waste treatment methods
- $\cdot \textbf{Recommendation} \ \text{Must not be disposed together with household garbage.} \ Do \ not \ allow \ product \ to \ reach \ sewage \ system.$

· European waste catalogue		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
15 01 07	glass packaging	
HP3	Flammable	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP14	Ecotoxic	

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (TURPENTINE), MARINE POLLUTANT PAINT
· 14.3 Transport hazard class(es)	
ADR, IMDG	
Class	3 Flammable liquids.
· Label	3
IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances: Solvent naphtha (petroleum), light arom. Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-E
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Mai and the IBC Code	rpol Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1.0 Printing date 17.11.2020 Revision: 17.11.2020

(Contd. of page 6)

· UN "Model Regulation":

UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H228 Flammable solid.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product Safety Department
- · Contact: B. Treiber, b.treiber@c-kreul.de
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3 Flam. Sol. 1: Flammable solids – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2