

Printing date 20.10.2022 Version number 1.3 (replaces version 1.2) Revision: 20.10.2022

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: KREUL Foto Transfer Potch Varnish Gloss 50 ml
- · Article number: 49981
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Lacquer

For artists and hobby user.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

GERMANY

Phone: +49 (0) 9545/925 - 0

Fax: + 49 (0) 9545/925 - 511

info@c-kreul.de

· Further information obtainable from:

Product Safety Department:

Treiber, b.treiber@c-kreul.de

1.4 Emergency telephone number:

Phone: +49 (0) 9545/925 - 0

Fax: + 49 (0) 9545/925 - 511

(Monday - Thursday 8.00 - 17.00, Friday 8.00 - 15.00)

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- Signal word Void
- · Hazard statements Void
- Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-octyl-2H-isothiazol-3-one, 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	ene glycol nce with a Community workplace exposure limit	2.5–<5%

(Contd. on page 2)

Printing date 20.10.2022 Version number 1.3 (replaces version 1.2) Revision: 20.10.2022

CAS: 2634-33-5	1.2 honzinathiczal 2/2H) and	(Contd. of page <0.05%
EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Acute Tox. 1, H330; Eye Dam. 1, H318; Aquatic Acute 1,	<0.05%
	H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit.	
	2, H315; Skin Sens. 1, H317	
	Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	
CAS: 55965-84-9	5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-	0.00025-<0.0015
Index number: 613-167-00-5	3-one (3:1)	
	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330;	
	Skin Corr. 1C, H314; Eye Dam. 1, H318; & Aquatic Acute 1,	
	H400 (M=100); Aquatic Chronic 1, H410 (M=100); ♦ Skin Sens.	
	1A, H317	
	Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 %	
	Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6	
	% For Day 4.11040.0 > 0.0 %	
	Eye Dam. 1; H318: C ≥ 0.6 %	
	Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	
040,00500,00.4	·	0.00005 +0.0045
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one	0.00025-<0.0015
Index number: 613-112-00-5	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330;	
index number. 613-112-00-5	Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. S	
	1A, H317, EUH071	
	ATE: LD50 oral: 125 mg/kg	
	LD50 dermal: 311 mg/kg	
	LC50/4h inhalative: 0.27 mg/m³	
	Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	

4 First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Wash with water and acidic soap.

Generally the product does not irritate the skin.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses.

After swallowing:

If symptoms persist consult doctor.

Rinse out mouth and then drink plenty of water.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment: No special measures required.
- · Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GE

Printing date 20.10.2022 Version number 1.3 (replaces version 1.2) Revision: 20.10.2022

(Contd. of page 2)

7 Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

No special measures required.

The product is not flammable.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.

Ingredients with limit values that require monitoring at the workplace:

· Further information about storage conditions:

Protect from frost.

Protect from heat and direct sunlight.

- · Storage class: 12
- · 7.3 Specific end use(s) See chapter 1.2.

8 Exposure controls/personal protection

· 8.1 Control parameters

57-55-6 P	ropylene glycol			
WEL Lon	WEL Long-term value: 474* 10** mg/m³, 150* ppm *total vapour and particulates **particulates			
· DNELs				
57-55-6 P	ropylene glycol			
Inhalative	chronic - local effect	10 mg/m³ /long-term (general population)		
		10 mg/m³ /long-term (worker)		
	chronic - systemic effect	50 mg/m³ /long term (general population)		
	-	168 mg/m³ /long-term (worker)		
·PNECs	-			
57-55-6 P	ropylene glycol			
water	1183	ma/l		

water	183 mg/l
freshwater	183 mg/l 260 mg/l
marine water	26 mg/l
sewage treatment plant (STP)	20,000 mg/l
freshwater sediment	572 mg/kg 57.2 mg/kg
marine sediment	57.2 mg/kg
soil	50 mg/kg

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Not required.

Use suitable respiratory protective device only when aerosol or mist is formed.

Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Goggles recommended during refilling

9 Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information

Physical state Fluid

(Contd. on page 4)

Version number 1.3 (replaces version 1.2) Revision: 20.10.2022 Printing date 20.10.2022

(Contd. of page 3) · Colour: According to product specification Odour: Characteristic Odour threshold: Not determined. Melting point/freezing point: Undetermined. Boiling point or initial boiling point and boiling range Undetermined. · Flammability Not applicable. Lower and upper explosion limit Not determined. · Lower: · Upper: Not determined. Flash point: Not applicable. Decomposition temperature: Not determined. pH at 20 °C 6-9 Viscosity: Kinematic viscosity Not determined · Dynamic: Not determined. Solubility water: Fully miscible. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined. · Density and/or relative density · Density at 20 °C: ~1 g/cm³ Relative density Not determined. · Vapour density Not determined. 9.2 Other information Appearance: Fluid Form: Important information on protection of health and environment, and on safety. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Change in condition Evaporation rate Not determined. · Information with regard to physical hazard classes **Explosives** Void Flammable gases Void **Aerosols** Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void

10 Stability and reactivity

Desensitised explosives

Organic peroxides

Corrosive to metals

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

Void

Void

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values re	levant for classification:
57-55-6 P	ropylene	glycol
Oral	LD50	22,000 mg/kg (rat) (ECHA)
Dermal	LD50	>2,000 mg/kg (rabbit) (ECHA)

(Contd. on page 5)

Revision: 20.10.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.10.2022 Version number 1.3 (replaces version 1.2)

(Contd. of page 4) 2634-33-5 1,2-benzisothiazol-3(2H)-one LD50 490 mg/kg (rat) Oral LD50 >2,000 mg/kg (rat) Dermal Inhalative LC50/4h 0.05 mg/m³ (ATE) 55965-84-9 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) LD50 Oral 64 mg/kg (rat) LD50 87 mg/kg (rab) Dermal Inhalative LC50/4h 0.05 mg/m³ (ATE) 26530-20-1 2-octyl-2H-isothiazol-3-one Oral LD50 125 mg/kg (ATE) 760 mg/kg (rat) Dermal LD50 311 mg/kg (ATE) 690 mg/kg (rab) LC50/4h 0.27 mg/m³ (ATE) Inhalative 1.25 mg/m3 (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

Aquatic tox	<u> </u>
57-55-6 Pro	pylene glycol
LC50/96h	40,613 mg/l (oncorhynchus mykiss) (ECHA)
LC50/48h	18,340 mg/l (ceriodaphnia dubia) (ECHA)
ErC50/72h	19,300 mg/l (sceletonema costatum) (ECHA)
NOEC/18h	>20,000 mg/l (pseudomonas putida) (ECHA)
NOEC/7d	13,020 mg/l (ceriodaphnia dubia) (ECHA)
	<5,300 mg/l (sceletonema costatum) (ECHA)
2634-33-5 1	,2-benzisothiazol-3(2H)-one
LC50/96h	1.6 mg/l (oncorhynchus mykiss)
EC50/48h	2.94 mg/l (daphnia magna)
EC50/72h	0.11 mg/l (selenastrum capricornutum)
EC10/72h	0.04 mg/l (selenastrum capricornutum)
ErC50/72h	0.11 mg/l (pseudokirchneriella subcapitata)
NOEC/21d	1.2 mg/l (daphnia)
NOEC/72h	0.027 mg/l (sceletonema costatum)
NOEC/28d	0.21 mg/l (oncorhynchus mykiss)
55965-84-9	5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
LC50/96h	0.22 mg/l (oncorhynchus mykiss) (RAC)
EC50/48h	0.1 mg/l (daphnia magna)
EC50/72h	0.048 mg/l (pseudokirchneriella subcapitata)
	0.004 mg/l (daphnia magna) (OECD 211)
ErC50	0.0049 mg/l /120h (sceletonema costatum)
NOEC/21d	0.004 mg/l (daphnia)
NOEC/48d	0.00064 mg/l (sceletonema costatum)
NOEC/72h	0.0012 mg/l (pseudokirchneriella subcapitata) (OECD 201)
	0.098 mg/l (oncorhynchus mykiss) (OECD 210)
	2-octyl-2H-isothiazol-3-one
LC50/96h	0.047 mg/l (oncorhynchus mykiss)
EC50/48h	0.32 mg/l (daphnia magna)

- GB

Printing date 20.10.2022 Version number 1.3 (replaces version 1.2) Revision: 20.10.2022

(Contd. of page 5)

57-55-6 Propylene glycol

Carbon dioxide production 81.7 % /28d (OECD 301 F)
DOC removal 98.3 % /28d (OECD 301 F)
Oxygen consumption 106.8 % /28d (OECD 301 F)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Packaging may be reused or recycled after cleaning.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

14.2 UN proper shipping name	ot regulated	
14.2 UN proper shipping name	ot regulated	
ADR, ADN, IMDG, IATA no		
	ot regulated	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	ot regulated	
14.4 Packing group		
ADR, IMDG, IATA no	ot regulated	
14.5 Environmental hazards: No	ot applicable.	
14.6 Special precautions for user No.	ot applicable.	
· 14.7 Maritime transport in bulk according to IMO		
instruments No	ot applicable.	
UN "Model Regulation":	ot regulated	

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.

(Contd. on page 7)

Version number 1.3 (replaces version 1.2) Printing date 20.10.2022 Revision: 20.10.2022

(Contd. of page 6)

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Department issuing SDS: Product Safety Department

Contact: B. Treiber, b.treiber@c-kreul.de Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 3: Acute toxicity - Category 3
Acute Tox. 4: Acute toxicity - Category 4
Acute Tox. 2: Acute toxicity - Category 2
Acute Tox. 1: Acute toxicity - Category 2
Acute Tox. 1: Skin corrosion/irritation - Category 1
Skin Corr. 1: Skin corrosion/irritation - Category 1
Skin Irrit. 2: Skin corrosion/irritation - Category 1
Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eve Dam. 1: Serious eve damage/eve irritation - Category

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.