

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2023 Version number 1.5 (replaces version 1.4) Revision: 18.07.2023

# 1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: KREUL Acrylic gloss varnish 150 ml, 400 ml
- · Article number: 810150, 810400
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Lacquer

For artists and hobby user.

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

**GERMANY** 

Phone: +49 (0) 9545/925 - 0

Fax: +49 (0) 9545/925 - 511

info@c-kreul.de

· Further information obtainable from:

**Product Safety Department:** 

Treiber, b.treiber@c-kreul.de

· 1.4 Emergency telephone number: + 44 (0) 171 635 91 91

# 2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Dam. 1 H318 Causes serious eye damage.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms









GHS02 G

GHS05 GHS07

GHS09

· Signal word Danger

(Contd. on page 2)

Printing date 18.07.2023 Version number 1.5 (replaces version 1.4) Revision: 18.07.2023

(Contd. of page 1)

#### · Hazard-determining components of labelling:

butan-1-ol

hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclenes

hydrocarbons C6-C7, isoalkanes, cyclenes, <5% n-hexane

hydrocarbons C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics

#### Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with regional regulations.

#### Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

# 3 Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-XXXX	dimethyl ether  Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-<50%	
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-XXXX	butan-1-ol  ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	20-<25%	
EC number: 920-750-0 Reg.nr.: 01-2119473851-33-XXXX	hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclenes Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	12.5-<20%	
EC number: 926-605-8 Reg.nr.: 01-2119473851-33-XXXX	hydrocarbons C6-C7, isoalkanes, cyclenes, <5% n-hexane  Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411;  STOT SE 3, H336	5-<10%	
EC number: 927-241-2 Reg.nr.: 01-2119471843-32-XXXX	hydrocarbons C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics  Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic	5-<10%	

#### · Additional information:

Benzene (EINECS 200-753-7) < 0.1%. (Note P Annex VI to Directive (EC) No 1272/2008)

For the wording of the listed hazard phrases refer to section 16.

# 4 First aid measures

#### · 4.1 Description of first aid measures

· General information:

Take affected persons out into the fresh air.

In case of irregular breathing or respiratory arrest provide artificial respiration.

#### After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Seek immediate medical advice.

#### After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### After eve contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

Remove contact lenses.

(Contd. on page 3)

(Contd. of page 2)

# Safety data sheet

# according to 1907/2006/EC, Article 31

Printing date 18.07.2023 Version number 1.5 (replaces version 1.4) Revision: 18.07.2023

· After swallowing:

If symptoms persist consult doctor.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

# 6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2B
- · 7.3 Specific end use(s) See chapter 1.2.

## 8 Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.

(Contd. on page 4)

Version number 1.5 (replaces version 1.4) Printing date 18.07.2023 Revision: 18.07.2023

(Contd. of page 3)

· Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin

#### Respiratory protection:

Filter A2/P3

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

#### Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Not applicable, as aerosol.

1.5 Vol % (71-36-3 butan-1-ol)

26.2 Vol % (115-10-6 dimethyl ether)

Not applicable.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level ≤ 8h

As protection from splashes gloves made of the following materials are suitable:

Butvl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level ≤ 8h

Eye/face protection



Tightly sealed goggles

# 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

· Physical state Aerosol Colour: Colourless Odour: Characteristic Odour threshold: Not determined. Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling range

· Flammability

Lower and upper explosion limit

· Lower: · Upper:

Not applicable, as aerosol. Flash point: Auto-ignition temperature: 240 °C · Decomposition temperature: Not determined. Hq · Not determined.

· Viscosity:

Kinematic viscosity Not determined. Dynamic: Not determined.

Solubility

· water: Not miscible or difficult to mix. Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 4.000 hPa · Density and/or relative density Density at 20 °C: 0.7 g/cm<sup>3</sup> Relative density

Not determined. Vapour density Not determined.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2023 Version number 1.5 (replaces version 1.4)

(Contd. of page 4)

Revision: 18.07.2023

	(Contd. of page
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of hea	alth and
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Not determined.
Solvent content:	
Organic solvents:	95.8 %
VOC (EC)	95.80 %
Solids content:	4.1 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard clas	202
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container: May bur
A0100010	if heated
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammab	
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

Void

# 10 Stability and reactivity

**Desensitised explosives** 

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 \	· LD/LC50 values relevant for classification:		
115-10-6 c	115-10-6 dimethyl ether		
Inhalative	Inhalative LC50/4h 308 mg/m³ (rat)		
71-36-3 bu	71-36-3 butan-1-ol		
Oral	LD50	790 mg/kg (rat)	
Dermal	LD50	3,400 mg/kg (rabbit)	
Inhalative	LC50/4h	8,000 mg/m³ (rat)	
hydrocarb	hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclenes		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,800 mg/kg (rat)	
Inhalative	LC50/4h	22 mg/m³ (rat)	
hydrocarb	hydrocarbons C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics		
Oral	LD50	>15,000 mg/kg (rat)	
Dermal	LD50	>3,160 mg/kg (rabbit)	
Inhalative		>6,100 mg/m³ (rat)	

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 6)

Version number 1.5 (replaces version 1.4) Revision: 18.07.2023 Printing date 18.07.2023

(Contd. of page 5)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- **Endocrine disrupting properties**

None of the ingredients is listed.

# 12 Ecological information

#### · 12.1 Toxicity

· Aquatic toxicity:				
115-10-6 c	limethyl ether			
LC50/96h	>4,000 mg/l (fish)			
LC50/48h	>4,000 mg/l (daphnia magna)			
EC50/96h	155 mg/l (algae)			
71-36-3 bu	itan-1-ol			
LC50/96h	1,376 mg/l (fish)			
hydrocarb	ons C7-C9, n-alkanes, isoalkanes, cyclenes			
LC50/96h	>13.4 mg/l (oncorhynchus mykiss)			
LC50/48h	3 mg/l (daphnia magna)			
LC50/72h	20 mg/l (pseudokirchneriella subcapitata)			

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

# 13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

# **14 Transport information**

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
· ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· IMDG	AEROSOLS (hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclenes,
	hydrocarbons, C7-C9), MARINE POLLUTANT
· IATA	AFROSOLS flammable

- · 14.3 Transport hazard class(es)
- · ADR



Class 2 5F Gases.

(Contd. on page 7)

Version number 1.5 (replaces version 1.4) Revision: 18.07.2023 Printing date 18.07.2023

	(Contd. of page
Label	2.1
IMDG	
Class Label	2.1 Gases. 2.1
IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Product contains environmentally hazardous substances: hydrocarbor C6-C7, isoalkanes, cyclenes, <5% n-hexane
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Gases.
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category AFOR FOR AEROSOLS with a capacity above 1 litre: Category B. For WAST
Segregation Code	AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk according to IMC instruments	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0
Transport category Tunnel restriction code	Not permitted as Excepted Quantity 2 D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

# 15 Regulatory information

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

• Seveso category
P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Version number 1.5 (replaces version 1.4) Printing date 18.07.2023 Revision: 18.07.2023

(Contd. of page 7)

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

Extremely flammable gas. H220

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

May be fatal if swallowed and enters airways. H304

H315 Causes skin irritation.

H318 Causes serious eye damage.

May cause respiratory irritation. H335

May cause drowsiness or dizziness. H336

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Department issuing SDS: Product Safety Department

Contact: B. Treiber, b.treiber@c-kreul.de

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

\* Data compared to the previous version altered.