

.....

Printing date 21.11.2022 Version number 1.1 (replaces version 1.0) Revision: 21.11.2022

### 1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: KREUL Acrylic Matt Varnish water-based 50 ml, 275 ml
- · Article number: 79403, 79415
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Lacquer

For artists and hobby user.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

**GERMANY** 

Phone: +49 (0) 9545/925 - 0

Fax: +49 (0) 9545/925 - 511

info@c-kreul.de

· Further information obtainable from:

**Product Safety Department:** 

Treiber, b.treiber@c-kreul.de

1.4 Emergency telephone number:

Phone: +49 (0) 9545/925 - 0

Fax: + 49 (0) 9545/925 - 511

(Monday - Thursday 8.00 - 17.00, Friday 8.00 - 15.00)

### 2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:

- 1). May produce an allergic reaction.
- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · 3.2 Mixtures
- Description:

Mixture of substances listed below with nonhazardous additions.

Mixture based on water, binders and additeves.

· Dangerous components:		
CAS: 57-55-6	Propylene glycol	2.5-<5%
EINECS: 200-338-0	substance with a Community workplace exposure limit	
Reg pr : 01_2110456800_23_XXXX		

(Contd. on page 2)

Printing date 21.11.2022 Version number 1.1 (replaces version 1.0) Revision: 21.11.2022

		(Contd. of page 1
EINECS: 220-120-9 Index number: 613-088-00-6 Reg.nr.: 01-2120761540-60-XXXX	1,2-benzisothiazol-3(2H)-one  Acute Tox. 1, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317  Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	0.005-<0.05%
Index number: 613-167-00-5	5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317  Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	0.00025-<0.0015%

### 4 First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses.

Rinse opened eye for several minutes under running water.

After swallowing:

If symptoms persist consult doctor.

Rinse out mouth and then drink plenty of water.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5 Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
- Under certain fire conditions, traces of other toxic gases cannot be excluded.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

No special measures required.

The product is not flammable.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 3)

Printing date 21.11.2022 Version number 1.1 (replaces version 1.0) Revision: 21.11.2022

(Contd. of page 2)

· Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about storage conditions:

Protect from frost.

Protect from heat and direct sunlight.

- · Storage class: 12
- · 7.3 Specific end use(s) See chapter 1.2.

### 8 Exposure controls/personal protection

· 8.1 Control parameters

· Ingredien	ts with limit values that	require monitoring at the workplace:
57-55-6 Pr	ropylene glycol	
	g-term value: 474* 10** m al vapour and particulates	
· DNELs		
57-55-6 Pr	ropylene glycol	
Inhalative	chronic - local effect	10 mg/m³ /long-term (general population)
		10 mg/m³ /long-term (worker)
	chronic - systemic effect	50 mg/m³ /long term (general population)
	-	168 mg/m³ /long-term (worker)

P	N	F	$\overline{C}$

#### 57-55-6 Propylene glycol

water	183 mg/l
freshwater	260 mg/l
marine water	26 mg/l
sewage treatment plant (STP)	20,000 mg/l
freshwater sediment	572 mg/kg
marine sediment	57.2 mg/kg
soil	50 mg/kg

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

- Wash hands before breaks and at the end of work.

  Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.
- Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Goggles recommended during refilling

### 9 Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
Colourless
Characteristic
Not determined
Undetermined

Boiling point or initial boiling point and boiling range

100 °C (7732-18-5 water, distilled, conductivity or of similar

purity)

Flammability Not applicable.

Lower and upper explosion limit

· Lower: Not determined.

(Contd. on page 4)

Printing date 21.11.2022 Version number 1.1 (replaces version 1.0) Revision: 21.11.2022

(Contd. of page 3) Not determined. · Upper: Flash point: Not applicable Decomposition temperature: Not determined. pH at 20 °C Viscosity: · Kinematic viscosity Not determined. Dynamic: Not determined. Solubility · water: Fully miscible. Partition coefficient n-octanol/water (log value) Not determined · Vapour pressure at 20 °C: 23 hPa (7732-18-5 water, distilled, conductivity or of similar purity) Density and/or relative density Density at 20 °C: 1.1 a/cm<sup>3</sup> Relative density Not determined. Vapour density Not determined. 9.2 Other information Appearance: Form: Fluid · Important information on protection of health and environment, and on safety. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Change in condition · Evaporation rate Not determined. Information with regard to physical hazard classes Explosives Void Flammable gases Void Aerosols Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void Organic peroxides Void

### 10 Stability and reactivity

· Desensitised explosives

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

Corrosive to metals

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

Void

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rel	levant for classification:
57-55-6 P	ropylene	glycol
Oral	LD50	22,000 mg/kg (rat) (ECHA)
Dermal	LD50	>2,000 mg/kg (rabbit) (ECHA)
2634-33-5	1,2-benz	isothiazol-3(2H)-one
Oral	LD50	490 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4h	0.05 mg/m³ (ATE)
55965-84	-9 5-chlor	o-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Oral	LD50	64 mg/kg (rat)
	•	(Contd. on page 5

ntd. on page

Printing date 21.11.2022 Version number 1.1 (replaces version 1.0) Revision: 21.11.2022

| Dermal | LD50 | 87 mg/kg (rab) | Inhalative | LC50/4h | 0.05 mg/m³ (ATE) |

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## 12 Ecological information

#### · 12.1 Toxicity

· Aquatic to	xicity:
57-55-6 Pro	ppylene glycol
LC50/96h	40,613 mg/l (oncorhynchus mykiss) (ECHA)
LC50/48h	18,340 mg/l (ceriodaphnia dubia) (ECHA)
ErC50/72h	19,300 mg/l (sceletonema costatum) (ECHA)
NOEC/18h	>20,000 mg/l (pseudomonas putida) (ECHA)
NOEC/7d	13,020 mg/l (ceriodaphnia dubia) (ECHA)
NOEC/14d	<5,300 mg/l (sceletonema costatum) (ECHA)
2634-33-5 °	1,2-benzisothiazol-3(2H)-one
LC50/96h	1.6 mg/l (oncorhynchus mykiss)
EC50/48h	2.94 mg/l (daphnia magna)
EC50/72h	0.11 mg/l (selenastrum capricornutum)
EC10/72h	0.04 mg/l (selenastrum capricornutum)
ErC50/72h	0.11 mg/l (pseudokirchneriella subcapitata)
NOEC/21d	1.2 mg/l (daphnia)
NOEC/72h	0.027 mg/l (sceletonema costatum)
NOEC/28d	0.21 mg/l (oncorhynchus mykiss)
	5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
LC50/96h	0.22 mg/l (oncorhynchus mykiss) (RAC)
EC50/48h	0.1 mg/l (daphnia magna)
EC50/72h	0.048 mg/l (pseudokirchneriella subcapitata)
NOEC	0.004 mg/l (daphnia magna) (OECD 211)
ErC50	0.0049 mg/l /120h (sceletonema costatum)
NOEC/21d	0.004 mg/l (daphnia)
NOEC/48d	0.00064 mg/l (sceletonema costatum)
NOEC/72h	0.0012 mg/l (pseudokirchneriella subcapitata) (OECD 201)

### · 12.2 Persistence and degradability

#### 57-55-6 Propylene glycol

Carbon dioxide production | 81.7 % /28d (OECD 301 F)

DOC removal | 98.3 % /28d (OECD 301 F)

Oxygen consumption | 106.8 % /28d (OECD 301 F)

NOEC/28d | 0.098 mg/l (oncorhynchus mykiss) (OECD 210)

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 13 Disposal considerations

- · 13.1 Waste treatment methods
- $\cdot \mbox{\bf Recommendation} \mbox{ Smaller quantities can be disposed of with household waste.} \\$

(Contd. on page 6)

Version number 1.1 (replaces version 1.0) Printing date 21.11.2022

(Contd. of page 5)

Revision: 21.11.2022

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number ADR, ADN, IMDG, IATA	not regulated
· · · ·	not regulated
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	not regulated
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	not regulated
14.4 Packing group	
ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according	g to IMO
instruments	Not applicable.
UN "Model Regulation":	not regulated

### 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

- Department issuing SDS: Product Safety Department
- · Contact: B. Treiber, b.treiber@c-kreul.de
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

INDO: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

ELINUS: European List of Notined Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

PB1: Persistent, Bioaccumulative and Toxic 
VPVB: very Persistent and very Bioaccumulative 
Acute Tox. 3: Acute toxicity — Category 3 
Acute Tox. 4: Acute toxicity — Category 4 
Acute Tox. 2: Acute toxicity — Category 2 
Acute Tox. 1: Acute toxicity — Category 1 
Skin Corr. 1C: Skin corrosion/irritation — Category 1C 
Skin Irrit. 2: Skin corrosion/irritation — Category 1C 
Skin Irrit. 2: Skin corrosion/irritation — Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.