

Printing date 18.07.2022 Version number 1.0 Revision: 18.07.2022

1 Identification

- · Product identifier
- · Trade name: KREUL Varnish matt 50 ml, 250 ml, 1000 ml
- · Article number: 86160, 86165, 86169
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Painting Medium

For artists and hobby user.

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

C. KREUL GmbH & Co. KG

Carl-Kreul-Straße 2

D-91352 HALLERNDORF

DEUTSCHLAND

Tel. + 49 (0)9545 / 925 - 0

Fax + 49 (0)9545 / 925 - 511

E-Mail: info@c-kreul.de

Importer

Zart Art Pty Ltd

48 Overseas Drive

Noble Park North 3174

VIC

Australia

Ph: 61 3 9890 1867 Fax: 61 3 9898 6527

- · Further information obtainable from: Ph: 61 3 9890 1867 Fax: 61 3 9898 6527
- · Emergency telephone number: Poison Centre 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02

011007

- · Signal word Warning
- Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

Printing date 18.07.2022 Version number 1.0 Revision: 18.07.2022

(Contd. of page 1)

P370+P378 In case of fire: Use CO2, powder or water spray for extinction.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|---|--|----------|
| CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics | | 50-<100% |
| EC number: 919-857-5 | ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336 | |
| CAS: 64742-95-6 Hydrocarbons, C9, aromatics 10 | | 10-<20% |
| EC number: 918-668-5 | Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336 | |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Wash with water and acidic soap.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water.

Remove contact lenses.

After swallowing:

If symptoms persist consult doctor.

Rinse out mouth and then drink plenty of water.

- · Information for doctor:
- $\cdot \textbf{Most important symptoms and effects, both acute and delayed} \ \ \text{No further relevant information available}.$
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 3)

Printing date 18.07.2022 Version number 1.0 Revision: 18.07.2022

(Contd. of page 2)

Protect from heat.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

· Further information about storage conditions:

Keep container tightly sealed.

- Protect from heat and direct sunlight.
- · Storage class: 3
- · Specific end use(s) See chapter 1.2.

8 Exposure controls and personal protection

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

| DNELs | DNELs 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics | | | | | |
|------------|--|-------------------------------------|--|--|--|--|
| 64742-48- | | | | | | |
| Oral | Oral long-term exposure-systemic effects 300 mg/kg (general population) | | | | | |
| Dermal | long-term exposure-systemic effects | 300 mg/kg bw/d (general population) | | | | |
| | | 300 mg/kg bw/d (worker) | | | | |
| Inhalative | long-term exposure-systemic effects | 900 mg/m³ (general population) | | | | |
| | | 1,500 mg/m³ (worker) | | | | |
| 64742-95- | 64742-95-6 Hydrocarbons, C9, aromatics | | | | | |
| Oral | long-term exposure-systemic effects | 11 mg/kg (general population) | | | | |
| Dermal | long-term exposure-systemic effects | 11 mg/kg bw/d (general population) | | | | |
| | | 25 mg/kg bw/d (worker) | | | | |
| Inhalative | long-term exposure-systemic effects | 32 mg/m³ (general population) | | | | |
| | | 150 mg/m³ (worker) | | | | |

- Additional information: The lists valid during the making were used as basis.
- Exposure controls
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level \leq 8 h

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.12 \text{ mm}$

Value for the permeation: Level \leq 2-4 h

Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- Appearance:

Form: Fluid
Odour: Characteristic
Odour threshold: Not determined

pH-value: Not determined.

(Contd. on page 4)

Printing date 18.07.2022 Version number 1.0 Revision: 18.07.2022

| | (Contd. of page | |
|--|---|--|
| Change in condition Melting point/freezing point: Initial boiling point and boiling range | Undetermined. : 155 °C | |
| Flash point: | >23 °C | |
| Flammability (solid, gas): | Not applicable. | |
| Ignition temperature: | <237 °C | |
| Decomposition temperature: | Not determined. | |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures a possible. | |
| Explosion limits: Lower: Upper: | 0.8 Vol % 7 Vol % | |
| Vapour pressure at 20 °C: | 3.2 hPa | |
| Density at 20 °C: Relative density Vapour density Evaporation rate | 0.87 g/cm³ Not determined. Not determined. Not determined. | |
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. | |
| Partition coefficient: n-octanol/water: | Not determined. | |
| Viscosity: Dynamic: Kinematic at 40 °C: | Not determined. >20.5 mm²/s | |
| Solvent content: Organic solvents: | 68.0 % | |
| Solids content: | 32.0 % | |
| Other information | No further relevant information available. | |

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- $\cdot \ \textbf{Incompatible materials:} \ No \ further \ relevant \ information \ available.$
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity

| · LD/LC50 values relevant for classification: | | | | |
|--|--|--------------------|--|--|
| 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics | | | | |
| Oral LD50 >5,000 mg/kg (rat) | | | | |
| Dermal | LD50 | >5,000 mg/kg (rab) | | |
| Inhalative | LC50/4h | >4,951 mg/m³ (rat) | | |
| 64742-95- | 64742-95-6 Hydrocarbons, C9, aromatics | | | |
| Oral | LD50 | >6,800 mg/kg (rat) | | |
| Dermal | LD50 | >3,400 mg/kg (rab) | | |
| Inhalative | LC50/4h | >10.2 mg/m³ (rat) | | |

12 Ecological Information

· Toxicity

| Toxicity | | |
|--|--|--|
| · Aquatic toxicity: | | |
| 64742-95-6 Hydrocarbons, C9, aromatics | | |
| LC50/96h >1,000 mg/l (oncorhynchus mykiss) | | |
| EC50/48h >1,000 mg/l (daphnia magna) | | |

Persistence and degradability No further relevant information available.

(Contd. on page 5)

Printing date 18.07.2022 Version number 1.0 Revision: 18.07.2022

(Contd. of page 4)

- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| Transport information | |
|--|--|
| UN-Number ADG, IMDG, IATA | UN1263 |
| UN proper shipping name ADG IMDG, IATA | 1263 PAINT PAINT |
| Transport hazard class(es) | |
| ADG, IMDG, IATA | |
| | |
| Class Label | 3 Flammable liquids. 3 |
| Packing group ADG, IMDG, IATA | III |
| Environmental hazards: Marine pollutant: | Not applicable. Yes (DOT) |
| Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category | Warning: Flammable liquids. 30 F-E, <u>S-E</u> A |
| Transport in bulk according to Annex II of Marpol an IBC Code | nd the Not applicable. |
| Transport/Additional information: | |
| ADG Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| Transport category Tunnel restriction code | 3 D/E |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation": | UN 1263 PAINT, 3, III |

Version number 1.0 Printing date 18.07.2022 Revision: 18.07.2022

(Contd. of page 5)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Australian Inventory of Industrial Chemicals

We confirm that they we are have checked the AICS under here https://www.industrialchemicals.gov.au/search-inventory and we can confirm that each ingredient is either listed on the AICS and within the allowable limit or meets restrictions on said ingredient.

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

Australia: Priority Existing Chemicals

None of the ingredients is listed.

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms





GHS07

- · Signal word Warning
- Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use CO2, powder or water spray for extinction.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Contact: Ph: 61 3 9890 1867 Fax: 61 3 9898 6527

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

VPUB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3