

Safety Data Sheet
according to WHS Regulations

Printing date 26.07.2022

Version number 1.2

Revision: 26.07.2022

1 Identification

- **Product identifier**
- **Trade name:** SOLO GOYA Fixative-Spray 150 ml, 400 ml
- **Article number:** 800150, 800400
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Lacquer
For artists and hobby user.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
C. KREUL GmbH & Co. KG
Carl-Kreul-Straße 2
D-91352 HALLERNDORF
DEUTSCHLAND
Tel. + 49 (0)9545 / 925 - 0
Fax + 49 (0)9545 / 925 - 511
E-Mail: info@c-kreul.de
- **Importer**
Zart Art Pty Ltd
48 Overseas Drive
Noble Park North 3174
VIC
Australia
Ph: 61 3 9890 1867 Fax: 61 3 9898 6527
- **Further information obtainable from:** Ph: 61 3 9890 1867 Fax: 61 3 9898 6527
- **Emergency telephone number:** Poison Centre 13 11 26

2 Hazard(s) Identification

- **Classification of the substance or mixture**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
n-butyl acetate
acetone
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 26.07.2022

Version number 1.2

Revision: 26.07.2022

(Contd. of page 1)

- P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe spray.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary measures against static discharges.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8	dimethyl ether ⚠ Flam. Gas 1A, H220; ⚠ Press. Gas C, H280	25-<50%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H336	2.5-<5%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319	<2.5%
CAS: 1330-20-7 EC number: 905-588-0 Index number: 601-022-00-9	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; ⚠ Skin Irrit. 2, H315	<2.5%
CAS: 9004-70-0	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose ⚠ Flam. Sol. 1, H228	<2.5%

Additional information:

Benzene (EINECS 200-753-7) <0.1%. (Note P Annex VI to Directive (EC) No 1272/2008)
 For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Wash with water and acidic soap.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Remove contact lenses.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Seek immediate medical advice.
A person vomiting while laying on their back should be turned onto their side.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
If swallowed or in case of vomiting, danger of entering the lungs.

5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fire with alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

AU
(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 26.07.2022

Version number 1.2

Revision: 26.07.2022

(Contd. of page 2)

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
 Ensure adequate ventilation
 Use respiratory protective device against the effects of fumes/dust/aerosol.
 Keep away from ignition sources.
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Send for recovery or disposal in suitable receptacles.
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**
 Take note of emission threshold.
 Keep away from heat and direct sunlight.
 Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 Do not spray onto a naked flame or any incandescent material.
 Fumes can combine with air to form an explosive mixture.
 Keep ignition sources away - Do not smoke.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Store receptacle in a well ventilated area.
 Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
 Keep container tightly sealed.
- **Storage class:** 2B
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WES	Short-term value: 950 mg/m ³ , 500 ppm
	Long-term value: 760 mg/m ³ , 400 ppm

123-86-4 n-butyl acetate

WES	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 713 mg/m ³ , 150 ppm

67-64-1 acetone

WES	Short-term value: 2375 mg/m ³ , 1000 ppm
	Long-term value: 1185 mg/m ³ , 500 ppm

64-17-5 ethanol

WES	Long-term value: 1880 mg/m ³ , 1000 ppm
-----	--

1330-20-7 xylene

WES	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 350 mg/m ³ , 80 ppm

- **DNELs**

64-17-5 ethanol

Oral	long-term exposure-systemic effects	87 mg/kg (general population)
Dermal	long-term exposure-systemic effects	206 mg/kg bw/d (general population) 343 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	114 mg/m ³ (general population) 950 mg/m ³ (worker)

- **PNECs**

64-17-5 ethanol

water	2.75 mg/l
freshwater	0.96 mg/l

(Contd. on page 4)

AU

Safety Data Sheet

according to WHS Regulations

Printing date 26.07.2022

Version number 1.2

Revision: 26.07.2022

(Contd. of page 3)

marine water	0.79 mg/l
sewage treatment plant (STP)	580 mg/l
freshwater sediment	3.6 mg/kg
soil	0.63 mg/kg

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

PVC or PE gloves

Value for the permeation: Level \leq 8 h

Recommended thickness of the material: \geq - mm

· **As protection from splashes gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material: \geq 0.3 mm

Value for the permeation: Level \leq 1-2 h

· **Eye protection:** Not required.

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Aerosol
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 240 °C

· **Decomposition temperature:** Not determined.

· **Explosive properties:** Not determined.

· **Explosion limits:**

· Lower:	1.2 Vol %
· Upper:	26 Vol %

· **Vapour pressure at 20 °C:** 4,000 hPa

· **Density at 20 °C:** ~0.7 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

water: Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**

· Organic solvents:	94.6 %
· VOC (EC)	94.60 %

· **Solids content:** 4.9 %

(Contd. on page 5)

AU

Safety Data Sheet

according to WHS Regulations

Printing date 26.07.2022

Version number 1.2

Revision: 26.07.2022

(Contd. of page 4)

Other information

No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

LD/LC50 values relevant for classification:
ATE (Acute Toxicity Estimates)

Dermal	LD50	>80,000 mg/kg (rabbit)
--------	------	------------------------

115-10-6 dimethyl ether

Inhalative	LC50/4h	308 mg/m ³ (rat)
------------	---------	-----------------------------

123-86-4 n-butyl acetate

Oral	LD50	10,800 mg/kg (rat)
Dermal	LD50	>17,600 mg/kg (rabbit)
Inhalative	LC50/4h	>21 mg/m ³ (rat)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	>15,800 mg/kg (rabbit)
Inhalative	LC50/4h	76 mg/m ³ (rat)

64-17-5 ethanol

Oral	LD50	10,470 mg/kg (rat) (OECD 403)
Dermal	LD50	>2,000 mg/kg (rat) 12,800 mg/kg (rabbit)
Inhalative	LC50/4h	124.7 mg/m ³ (rat) (OECD 403)

1330-20-7 xylene

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4h	21.7 mg/m ³ (rat)

12 Ecological Information

- **Toxicity**

Aquatic toxicity:
115-10-6 dimethyl ether

LC50/96h	>4,000 mg/l (fish)
LC50/48h	>4,000 mg/l (daphnia magna)
EC50/96h	155 mg/l (algae)

123-86-4 n-butyl acetate

LC50/96h	81 mg/l (fish)
----------	----------------

67-64-1 acetone

LC50/96h	8,300 mg/l (fish)
LC50/48h	8,450 mg/l (crustaceans)
EC50/96h	7,200 mg/l (algae)

64-17-5 ethanol

LC50/96h	14,200 mg/l (pimephales promelas) (US EPA method E03-0) 13,000 mg/l (oncorhynchus mykiss)
LC50/48h	5,012 mg/l (ceriodaphnia dubia) (ASTM E729-80) 12,340 mg/l (daphnia magna)

(Contd. on page 6)

AU

Safety Data Sheet

according to WHS Regulations

Printing date 26.07.2022

Version number 1.2

Revision: 26.07.2022

(Contd. of page 5)

EC50/48h	12,900 mg/l (algae) >10,000 mg/l (ceriodaphnia dubia) (DIN 38412 Teil 11) 9,950 mg/l (crustaceans)
EC50/96h	12,900 mg/l (pimephales promelas) (US EPA method E03-0)
NOEC	2 mg/l /10d (ceriodaphnia dubia) (ECHA) 250 mg/l /120h (danio rerio) (OECD 212)
ErC50	275 mg/l /72h (algae) (OECD 201)
ErCx 10%	11.5 mg/l /3d (algae) (OECD 201)
LC50	1,806 mg/l /10d (ceriodaphnia dubia) (ECHA) 454 mg/l /9d (daphnia magna) (ECHA)
1330-20-7 xylene	
LC50/96h	15.7 mg/l (fish)
LC50/48h	8.5 mg/l (crustaceans)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1950
· ADG, IMDG, IATA	
· UN proper shipping name	1950 AEROSOLS
· ADG	AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· Transport hazard class(es)	
· ADG	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1 Gases.
· Label	2.1
· Packing group	not regulated
· ADG, IMDG, IATA	
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre:

(Contd. on page 7)

Safety Data Sheet

according to WHS Regulations

Printing date 26.07.2022

Version number 1.2

Revision: 26.07.2022

(Contd. of page 6)

· Segregation Code	Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Australian Inventory of Industrial Chemicals**

We confirm that they we are have checked the AICS under here <https://www.industrialchemicals.gov.au/search-inventory> and we can confirm that each ingredient is either listed on the AICS and within the allowable limit or meets restrictions on said ingredient.

All ingredients are listed.

- **Standard for the Uniform Scheduling of Medicines and Poisons**

67-64-1	acetone	S5
1330-20-7	xylene	S6

- **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labelling:**

n-butyl acetate
acetone

- **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Sveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

(Contd. on page 8)

AU

Safety Data Sheet

according to WHS Regulations

Printing date 26.07.2022

Version number 1.2

Revision: 26.07.2022

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. of page 7)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H228 Flammable solid.
 H280 Contains gas under pressure; may explode if heated.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

· **Contact:** Ph: 61 3 9890 1867 Fax: 61 3 9898 6527

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 Press. Gas C: Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Sol. 1: Flammable solids – Category 1
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

-AU-