

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 1 of 15

1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Identification of the substance/preparation

Trade name AVANTGARDE Gutta solvent-based
Article No. 94401
Package size 50 ml
Substance name -
INDEX No. -
EG No. -
CAS No. -
REACH Registration No. -

1.2 Use of the substance/preparation

Ready to use lining paint for colorless lines. For artists and hobby user.

1.3 Manufacturer/Supplier

C. KREUL GmbH & Co. KG
Carl-Kreul-Strasse 2
D-91352 Hallerndorf
Phone no. +49 (0) 9545 925-0
Fax no. +49 (0) 9545 925-511
Mail info@c-kreul.de

Information provided by

Mrs. Treiber, b.treiber@c-kreul.de

1.4 Emergency information

Phone no. +49 (0) 9545 925-0
Fax no. +49 (0) 9545 925-511

(Monday - Thursday 8.00 - 17.00; Friday 8.00 - 15.00)

2. HAZARD IDENTIFICATION

2.1 Classification of the substance/preparation

Classification according to Regulation (EC) 1272/2008

According to Regulation (EC) 1272/2008 the product will be classified 2015 at the earliest.

Classification according to Regulation (EC) 67/548 or Regulation (EC) 1999/45

F R11, N R51/53, R66, R67

2.2 Labelling according to Regulation (EC) 1272/2008 or Regulation (EC) 1999/45

Labelling according to Regulation (EC) 1272/2008

Hazard pictogram and signal word of the product

According to Regulation (EC) 1272/2008 the product will be classified 2015 at the earliest.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 2 of 15

Hazard-determining components of labelling

-

Hazard statements

-

European hazard statements

EUH -

Precautionary statements

-

Labelling according to Regulation (EC) 67/548 or Regulation (EC) 1999/45
Danger symbol and danger designation of the product



Highly flammable



Dangerous for the environment

Hazard-determining components of labelling

-

Risk-phrases

- 11 Highly flammable.
51/53 Toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

Safety-phrases

- 2 Keep out of the reach of children.
23 Do not breathe fumes/aerosol.
29/56 Do not empty into the drains, dispose of this material and its container at hazardous or special waste collection point.
43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
46 If swallowed seek medical advice immediately and show this container or label.

2.3 Other Hazards

Contains isobutyl methacrylate. May produce an allergic reaction.
Highly flammable. Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical / electrical equipment). Take precautionary measures against static discharges.

Results of PBT and vPvB assessment: Not applicable.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 3 of 15

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization

Preparation based on resins and organic solvent.

Substance related information

The product is a preparation.

Main component

-

INDEX No. -

EG No. -

CAS No. -

REACH Registration No.: -

Classification according to Regulation (EC) 1272/2008: -

Classification according to Regulation (EC) 67/548 or Regulation (EC) 1999/45: -

Hazard impurities

-

INDEX No. -

EG No. -

CAS No. -

REACH Registration No.: -

Classification according to Regulation (EC) 1272/2008: -

Classification according to Regulation (EC) 67/548 or Regulation (EC) 1999/45: -

(Danger designation: -)

3.1 Preparation/mixture related information


50 - 75 % Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics)¹


INDEX No. 649-328-00-1

EG No. 265-151-9 (920-750-0)²

CAS No. 64742-49-0

REACH Registration No.: 01-2119473851-33-XXXX

Classification according to Regulation (EC) 1272/2008: 

Classification according to Regulation (EC) 67/548: 

(Danger designation: Highly flammable, Harmful, Dangerous for the environment)


< 0,5 % Isobutyl methacrylate

INDEX No. 607-113-00-X

EG No. 202-613-0

CAS No. 97-86-9




REACH Registration No.: -

Classification according to Regulation (EC) 1272/2008: 

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 4 of 15

Classification according to Regulation (EC) 67/548: R10,  Xi R36/37/38,  Xi R43,  N R50

(Danger designation: Flammable, Irritant, Dangerous for the environment)

*minimum classification

¹ Note P according to VO 1272/2008 applies to this product or to one or several of its components. Benzene concentration < 0,1 Gew-%. Classification and labeling as carcinogene (R45) is not necessary.

² The above mentioned EC No. is a specific under-group of the CAS No. which is a reference for international inventories.

Additional information: Every entry in the EC No. column which begins with number "9" is – up to the publication of the official registration number – a temporary number declared by the ECHA for the substance.

Full text of R-, H- and EUH-phrases: see section 16.

4. FIRST AID MEASURES

4.1 General information

Remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Immediately remove person concerned out of danger area. Symptoms see part 11.

After inhalation

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. If breathing is irregular or stopped, administer artificial respiration. Unconsciousness: lateral poison - contact a doctor immediately.

After skin contact

Remove contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do NOT use solvents or thinners. In case of skin reactions, consult a physician.

After eye contact

Remove contact lens. Irrigate copiously with clean, fresh water for at least 10 - 15 minutes, holding the eyelids apart and seek medical advice.

After ingestion

If swallowed immediately drink: water, to which activated charcoal may be added. Do NOT induce vomiting. During spontaneous vomiting hold the head of the casualty low with the body in a prone position in order to avoid aspiration. Call a physician to the site of the accident in every case.

4.2 The most important acute and delayed appearing symptoms and effects

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. See part 11.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 5 of 15

4.3 References to medical emergency relief or special treatment

With unconsciousness: inform an emergency doctor. Further instructions see section 4.1.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Extinguishing powder, foam, water spray and carbon dioxide.
Extinguishing media which must not be used for safety reasons: Full water jet

5.2 Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Use water spray jet to protect personnel and to cool endangered containers. Cool endangered containers with water in case of fire. It is possible to pressure formation and to burst of containers. Fire will produce dense black smoke. When product exposed to high temperatures it may produce hazardous decomposition products such as carbon monoxide and carbon dioxide, smoke and other hazards components.

5.3 Special protective equipment

In case of fire: Wear self-contained breathing apparatus. Use water spray jet to protect personnel and to cool endangered containers. Beware of reignition. Do not allow the quenching water into the sewage system. Dispose fire debris and contaminated fire fighting water in accordance with official regulations.

5.4 Additional information

Compare section 3, 7, 8 and 10.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions

Wear protective gloves/protective clothing/eye protection/face protection. Remove ignition sources. Provide for sufficient ventilation. Do NOT inhale the vapour. Remove persons to safety.

6.2 Environmental precautions

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not empty into drains or watercourses. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Further instructions see section 6.3.

6.3 Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents. Further instructions see part 10.

6.4 Additional information

Further instructions see section 7, 8 and 10.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 6 of 15

7. HANDLING AND STORAGE

7.1 Information for safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Provide adequate ventilation. Never use pressure to empty: container is not a pressure vessel. Do not leave vessels/containers open. Always keep in containers of same material as the original one. Additionally, the product should only be used in areas from which all-naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electro statically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Use only antistatic equipped (spark-free) tools. Comply with the health and safety at work laws (TRGS 500). Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in application area. See protective measures under point 8.

Precautions against fire and explosion

Highly flammable. Keep away from sources of ignition - No smoking. Danger of inflammation in cause of weldings-works at empty containers. Vapours may form explosive mixtures with air. Take precautionary measures against static discharges. Usual measures for fire prevention.

7.2 Conditions for safe storage, including incompatibilities

Information about storage conditions

Store between 5 and 30 °C in a dry, well-ventilated place away from sources of heat and direct sunlight. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep container tightly closed.

Hints on joint storage

Only substances of the same storage class should be stored together. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. The substance should not be stored with substances with which hazardous chemical reactions are possible.

Requirement for storage rooms and vessels

Store between 5 and 30 °C in a dry, well-ventilated place away from sources of heat and direct sunlight. No smoking. Keep container tightly closed. Containers, which are opened, must be carefully resealed and kept upright to prevent leakage. Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act. Observe label precautions.

Additional information

Storage class (VCI): 3A Flammable liquid substances

7.3 Specific uses

Ready to use lining paint for colorless lines. For artists and hobby user.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 7 of 15

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Components with critical values that require monitoring at the workplace (exposure limits)

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics)¹; CAS No. 64742-49-0

Specification: AGW
 Value: 100 ml/m³ (ppm)
 Peak limitation: -
 Toxic to reproduction: -
 Remark: Hydrocarbon mixture

Isobutyl methacrylate; CAS No. 97-86-9

Specification: MAK
 Value: 300 ml/m³ (ppm), 560 mg/m³
 Peak limitation: -
 Toxic to reproduction: -
 Remark: -

DNEL/DMEL-Values

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics)¹; CAS No. 64742-49-0

Oral	DNEL long-term exposure – systemic effects	699 mg/kg	(general population)
Dermal	DNEL long-term exposure – systemic effects	699 mg/kg bw/d	(general population)
		773 mg/kg bw/d	(worker)
Inhalativ	DNEL long-term exposure – systemic effects	608 mg/m ³	(general population)
		2035 mg/m ³	(worker)

PNEC-Values

No data available.

8.2 Occupational exposure controls

Technical measures and the application of suitable working methods have precedence before the application of personal protective equipment. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Suitable judgement methods of the examination of the effectiveness of the grievied preventive measures enclose measuring-technical and non-technical inquiry methods like they in the technical rules for danger materials (TRGS) 402.

Personal protective equipment

Do not eat or drink during work – No smoking. Keep away from foodstuffs and beverages. Wash hands before breaks and after work. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately.

Respiratory protection

Take breathing protection measures (see also instruct to avoid accidents). Breathing protection equipment required in inadequately ventilated places and during spraying.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 8 of 15

Respiratory filter (gas): A1 (brown) until 1000 ml/m³ (ppm)
A2 (brown) until 5000 ml/m³ (ppm)
A3 (brown) until 10000 ml/m³ (ppm)

Details are to be inferred "from the rules for the use of respiratory protective devices" (BGR 190 (German regulation)).

Skin protection

Avoid contact with skin. Use protective gloves (EN 374). Solvent-resistant protective gloves must be worn. The glove material must be sufficiently impermeable and resistant to the substance. Check the tightness before wear. Gloves should be well cleaned before being removed, then stored in a well ventilated location. Textile or leather gloves are completely unsuitable. Pay attention to skin care.

The following materials are suitable for protective gloves

Inherent protection

Nitrile rubber/Nitrile latex – NBR (0,4 mm): Permeation time >= 8 hours

Splash guard

Nitrile rubber/Nitrile latex – NBR (0,12 mm): Permeation time 2 - 4 hours

The times listed are suggested by measurements taken at 22 °C and constant contact. Temperatures raised by warmed substances, body heat, etc. and a weakening of the effective layer thickness caused by expansion can lead to a significantly shorter breakthrough time. In case of doubt contact the gloves' manufacturer. A 1.5-times increase / decrease in the layer thickness doubles / halves the breakthrough time. This data only applies to the pure substance. Transferred to mixtures of substances, these figures should only be taken as an aid to orientation.

Eye protection

Avoid contact with eyes. Use safety glasses according to EN 166:2001.

Body protection

Personnel should wear antistatic clothing's made of natural fibre or of high temperature resistant synthetic fibre. All parts of the body should be washed after contact. Light protective clothing.

Limitation and supervision of the environmental exposition

See section 6 and 7.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 General information

Form: liquid
Colour: crystal clear
Odour: like solvent

9.2 Relevant safety data

Flashpoint: approx. 2 °C DIN EN 22719
Viscosity: > 30 s ISO 2431

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 9 of 15

Density: (20 °C)	approx. 0,8 g/cm ³	DIN 53217
Explosive limits:		
Lower / Upper:	0,7 Vol.-% / 7 Vol.-%	
Ignition temperature:	> 200 °C	
Vapour pressure:	not determined (20 °C)	
pH-value:	not applicable	
Solubility in water:	insoluble	

9.3 Additional information

No other physical-chemical data available.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. See section 7.

10.2 Chemical stability

If handled properly then product has chemical stability.

10.3 Possible dangerous reactions

None, if handled according to order. Further instructions see section 10.1 and 10.2.

10.4 Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5 Incompatible materials

See section 10.1.

10.6 Hazardous decomposition products

When product exposed to high temperatures, it may produce hazardous decomposition products such as carbon monoxide and carbon dioxide, smoke and other hazardous components.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

There are no data available.

**Primary irritant effect
after inhalation**

Exposure to component solvents vapour concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 10 of 15

on the skin	Contains isobutyl methacrylate. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin and absorption through the skin.
on the eyes	There are no data available on the preparation itself.
after ingestion	Harmful: may cause lung damage if swallowed. Do not induce vomiting. For symptoms see primary irritant effect after inhalation.
Sensitization	There are no data available on the preparation itself.
Chronic	There are no data available on the preparation itself.

11.2 Additional toxicological information

The product is classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2 Persistence/degradability

There are no data available.

12.3 Bioaccumulative potential

There are no data available.

12.4 Mobility

There are no data available.

12.5 Results of PBT and vPvP assessment

There are no data available.

12.6 Other adverse effects

There are no data available.

12.7 Further ecological information

Do not discharge into the drains/surface waters/groundwater.
Water hazard class: WGK 2 hazardous to water

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Send to a hazardous waste incinerator facility under observation of official regulations. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 11 of 15

Recommendation

Disposal must be made according to official regulations.

13.2 European waste code number in accordance with AAV

EWC No.: 08 01 11 waste paint and varnish containing organic solvents or other dangerous
EWC No.: 20 01 27 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR
COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES)
INCLUDING SEPARATELY COLLECTED FRACTIONS, solvents

13.3 Packaging

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing, may be taken for reuse. Packaging that cannot be cleaned should be disposed in the same manner as the medium.

EWC No. 15 01 10 packaging containing residues of or contaminated by dangerous substances

Non-contaminated packages

EWC No.: 15 01 02 plastic packaging
EWC No.: 15 01 07 glass packaging

14. TRANSPORT INFORMATION

14.1 Land transport ADR/RID and GVS/GGVE



Class: 3 Flammable liquids
Kemler-Code: 33
UN No.: 1263
Packaging group: II
Label: 3
Special marking: yes, Symbol (fish and tree)
Proper shipping name: 1263 - (Naphtha (petroleum))
Classification-Code: F1
Limit: 5 L
Tunnel restriction code: 3 (D/E)

14.2 Maritime transport IMDG/GGVSea



Class: 3
UN No.: 1263
Label: 3

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 12 of 15

Packaging group: II
EmS-No.: F-E, S-E
Marine pollutant: yes
Proper shipping name: Paint (Naphtha (petroleum))

14.3 Air transport ICAO-TI and IATA-DGR



ICAO/IATA Class: 3
UN no.: 1263
Label: 3
Packaging group: II
Proper shipping name: Paint (Naphtha (petroleum))

14.3 Remarks

Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics)¹

15. REGULATORY INFORMATION

15.1 European Regulation

Chemical Safety Assessment: For this substance a chemical safety assessment is not required.

Labelling according to Regulation (EC) 67/548 or Regulation (EC) 1999/45

Danger symbol and danger designation of the product



Highly flammable



Dangerous for the environment

Risk-phrases

11 Highly flammable.
51/53 Toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

Safety-phrases

2 Keep out of the reach of children.
23 Do not breathe fumes/aerosol.
29/56 Do not empty into the drains, dispose of this material and its container at hazardous or special waste collection point.
43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
46 If swallowed seek medical advice immediately and show this container or label.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 13 of 15

Hazard-determining components of labelling

-

15.2. National Regulations

Statutory order on hazardous incidents (StörfallV): Annex I, Nr. 6, 9b
Regulation on inflammable liquids: VbF-Class: All
Emission control act ("TA-Luft"): 3.1.7 Class III
Water hazard class: WGK 2 hazardous to water (according VwVWS)

15.3. Additional information

Contains isobutyl methacrylate. May produce an allergic reaction.
Labelling according to Regulation (EC) 1272/2008: According to Regulation (EC) 1272/2008 the product will be classified 2015 at the earliest.
The product is classified according to the EEC directives and the Ordinance on Hazardous Materials (GefStoffV).
If bottle \leq 125 ml then the following R- and S-phrases are not necessary: 11-51/53-66-67, S 23-29/56-43.
Please check local regulations.
Volatile organic compounds (Swiss):
VOC-Gehalt (Schweiz): 59,6%, 23,8 g/50ml, 0,477 kg/l
The advertised use (section 1) is not subject of the Directive 2004/42/EC.

16. OTHER INFORMATION

16.1 Changes compared with the last version

The last version was all changed and revised completely. Alterations to the previous edition are marked in the right-hand margin.

16.2 Literature reference and data source

Regulation (EC) 1999/45, last changed by Regulation (EC) 1907/2006
Regulation (EC) 67/548, last changed by Regulation (EC) 2009/2
REACH Regulation (EC) 1907/2006, last changed by Regulation (EC) 453/2010
Regulation (EC) 1272/2008, last changed by Regulation (EC) 790/2009

Internet

<http://www.baua.de>
<http://www.arbeitssicherheit.de>
<http://www.gischem.de>

16.3 Full text of H- and R-phrases appearing in section 2 and 3:

According to Regulation (EC) 1272/2008

Flam. Liq. 2 H225	Highly flammable liquid and vapour.
Flam. Liq. 3 H226	Flammable liquid and vapour.
Asp. Tox. 1 H304	May be fatal if swallowed and enters airways.
Skin Irrit. 2 H315	Causes skin irritation.
Skin Sens. 1 H317	May cause an allergic skin reaction.
Eye Irrit. 2 H319	Causes serious eye irritation.
STOT SE 3 H335	May cause respiratory irritation.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 14 of 15

STOT SE 3 H336	May cause drowsiness or dizziness.
Aquatic Acute 1 H400	Toxic to aquatic life.
Aquatic Chronic 2 H411	Toxic to aquatic life with long lasting effects.

* minimum classification

EUH – statements

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) 67/548 or Regulation (EC) 1999/45:

10	Flammable.
11	Highly flammable.
36/37/38	Irritating to eyes, respiratory system and skin.
43	May cause sensitisation by skin contact.
50	May cause long-term adverse effects in the aquatic environment.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

Methods according to article 9 of the order (EC) No. 1272/2008 for the assessment of the information for the purpose of the classification were used:

Classification according to Regulation 67/548/EC and 1999/45/EC.

16.4 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

BImSchV: Order for the realisation of the Federal Immission Protection Law

CAS: Chemical Abstracts Service

DIN: Norm of the German institute of standardization

EC: Effective concentration

EC50: Effective concentration, 50 percent

EG: European Community

EINECS: European Inventory of Existing Commercial Chemical Substances

EN: European Standard

GefStoffV: Ordinance on Hazardous Substances, Germany

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Log K_{ow}: n-octanol-water partition coefficient

OECD: Organisation for Economic Co-operation and Development

PBT: Persistent, bioaccumulateable, toxically

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006
(revised by Regulation (EC) No. 453/2010)

AVANTGARDE Gutta solvent-based

Page 15 of 15

RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
TRGS:	Technical rules for danger materials
UN:	United Nations (Vereinte Nationen)
VOC:	Volatile Organic Compounds
vPvB:	very much persistent and very bioaccumulateable
VwVwS:	Administrative regulation of hazardous to waters materials
WGK:	Water hazardous class

16.5 Department issuing safety data sheet

Laboratory, Mrs. Dipl.-Ing. Treiber, b.treiber@c-kreul.de.

16.6 Additional information

The data is based on our present knowledge. The data correspond to the national and EEC legislation. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

It is not permitted to use the product for any other application mentioned in chapter 1 except with a written permission. The user is responsible for the compliance with all valid legal regulation.

This safety data sheet is only valid for AVANTGARDE Gutta solvent-based. It's not valid for other products placed in the according sales displays or sets.