



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 1 of 13**

**1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**1.1 Identification of the substance/preparation**

Trade name SOLO GOYA Clear lacquer  
Article No. 2271  
Package size 50 ml  
Substance name -  
INDEX No. -  
EG No. -  
CAS No. -  
REACH Registration No.-

**1.2 Use of the substance/preparation**

Colorless, fast-drying, non-sticking, semi-glossy coating lacquer for matt and glossy water-based colors. For artists and hobby user.

**1.3 Manufacturer/Supplier**

C. KREUL GmbH & Co. KG  
Carl-Kreul-Strasse 2  
D-91352 Hallerndorf  
Phone no. +49 (0) 9545 925-0  
Fax no. +49 (0) 9545 925-511  
Mail [info@c-kreul.de](mailto:info@c-kreul.de)

**Information provided by**

Mrs. Treiber, [b.treiber@c-kreul.de](mailto:b.treiber@c-kreul.de)

**1.4 Emergency information**

Phone no. +49 (0) 9545 925-0  
Fax no. +49 (0) 9545 925-511

(Monday - Thursday 8.00 - 17.00; Friday 8.00 - 15.00)

---

**2. HAZARD IDENTIFICATION**

**2.1 Classification of the substance/preparation**

**Classification according to Regulation (EC) 1272/2008**

Flam. Liq. 2 H225; Eye Irrit. 2 H319; STOT SE 3 H336; EUH066

**2.2 Labelling according to Regulation (EC) 1272/2008**

**Hazard pictogram and signal word of the product**



Danger



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 2 of 13**

**Hazard-determining components of labelling**

Ethyl acetate, CAS-Nr. 141-78-6.

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**European hazard statements**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P305+351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact  
338 lenses, if present and easy to do. Continue rinsing.  
P337+313 If eye irritation persists: Get medical advice/attention.  
P370+378 In case of fire: Use sand, CO<sub>2</sub>, dry powder for extinction.  
P501 Dispose of contents/container to hazardous or special waste collection point.

**2.3 Other Hazards**

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical / electrical equipment). Take precautionary measures against static discharges.

Results of PBT and vPvB assessment: Not applicable.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical characterization**

Preparation based on synthetic resins and ethyl acetate.

**Substance related information**

The product is a preparation.

**Main component**

-

**INDEX No.** -

**EG No.** -

**CAS No.** -

**REACH Registration No.:** -

**Classification according to Regulation (EC) 1272/2008:** -

**Hazard impurities**

-



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 3 of 13**

**INDEX No.** -  
**EG No.** -  
**CAS No.** -  
**REACH Registration No.:** -  
**Classification according to Regulation (EC) 1272/2008:** -

**3.1 Preparation/mixture related information**




**50 - 75 % Ethyl acetate**

**INDEX No.** 607-022-00-5

**EG No.** 205-500-4

**CAS No.** 141-78-6

**REACH Registration No.:** 01-2119475103-46-XXXX

**Classification according to Regulation (EC) 1272/2008:**  Flam. Liq. 3 H225;  Eye Irrit. 2 H319;  STOT SE 3 H336; EUH066

\*minimum classification

Full text of H- and EUH-phrases: see section 16.

---

**4. FIRST AID MEASURES**

**4.1 General information**

Remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Immediately remove person concerned out of danger area. Symptoms see part 11.

**After inhalation**

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. If breathing is irregular or stopped, administer artificial respiration. Unconsciousness: lateral poison - contact a doctor immediately.

**After skin contact**

Remove contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do NOT use solvents or thinners. In case of skin reactions, consult a physician.

**After eye contact**

Remove contact lens. Irrigate copiously with clean, fresh water for at least 10 - 15 minutes, holding the eyelids apart and seek medical advice.

**After ingestion**

If swallowed immediately drink: water, to which activated charcoal may be added. Do NOT induce vomiting. During spontaneous vomiting hold the head of the casualty low with the body in a prone position in order to avoid aspiration. Call a physician to the site of the accident in every case.



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 4 of 13**

**4.2 The most important acute and delayed appearing symptoms and effects**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. See part 11.

**4.3 References to medical emergency relief or special treatment**

With unconsciousness: inform an emergency doctor. Further instructions see section 4.1.

---

**5. FIRE-FIGHTING MEASURES**

**5.1 Extinguishing media**

Suitable extinguishing media: Extinguishing powder, foam, water spray and carbon dioxide.  
Extinguishing media which must not be used for safety reasons: Full water jet

**5.2 Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged**

Use water spray jet to protect personnel and to cool endangered containers. Cool endangered containers with water in case of fire. It is possible to pressure formation and to burst of containers. Fire will produce dense black smoke. When product exposed to high temperatures it may produce hazardous decomposition products such as carbon monoxide and carbon dioxide, smoke and other hazards components.

**5.3 Special protective equipment**

In case of fire: Wear self-contained breathing apparatus. Use water spray jet to protect personnel and to cool endangered containers. Beware of reignition. Do not allow the quenching water into the sewage system. Dispose fire debris and contaminated fire fighting water in accordance with official regulations.

**5.4 Additional information**

Compare section 3, 7, 8 and 10.

---

**6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions**

Wear protective gloves/protective clothing/eye protection/face protection. Remove ignition sources. Provide for sufficient ventilation. Do NOT inhale the vapour. Remove persons to safety.

**6.2 Environmental precautions**

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not empty into drains or watercourses. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Further instructions see section 6.3.

**6.3 Methods for cleaning up/collecting**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents. Further instructions see part 10.



## Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (revised by Regulation (EC) No. 453/2010)

SOLO GOYA Clear lacquer

Page 5 of 13

### 6.4 Additional information

Further instructions see section 7, 8 and 10.

## 7. HANDLING AND STORAGE

### 7.1 Information for safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Provide adequate ventilation. Never use pressure to empty: container is not a pressure vessel. Do not leave vessels/containers open. Always keep in containers of same material as the original one. Additionally, the product should only be used in areas from which all-naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electro statically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Use only antistatic equipped (spark-free) tools. Comply with the health and safety at work laws (TRGS 500). Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in application area. See protective measures under point 8.

#### Precautions against fire and explosion

Highly flammable liquid and vapour. Keep away from sources of ignition - No smoking. Danger of inflammation in cause of weldings-works at empty containers. Vapours may form explosive mixtures with air. Take precautionary measures against static discharges. Usual measures for fire prevention.

### 7.2 Conditions for safe storage, including incompatibilities

#### Information about storage conditions

Store between 5 and 30 °C in a dry, well-ventilated place away from sources of heat and direct sunlight. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep container tightly closed.

#### Hints on joint storage

Only substances of the same storage class should be stored together. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. The substance should not be stored with substances with which hazardous chemical reactions are possible.

#### Requirement for storage rooms and vessels

Store between 5 and 30 °C in a dry, well-ventilated place away from sources of heat and direct sunlight. No smoking. Keep container tightly closed. Containers, which are opened, must be carefully resealed and kept upright to prevent leakage. Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act. Observe label precautions.

#### Additional information

Storage class (VCI): 3A Flammable liquid substances



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 6 of 13**

**7.3 Specific uses**

See section 1.2.

---

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Components with critical values that require monitoring at the workplace (exposure limits)**

**Ethyl acetate; CAS No. 141-78-6**

Specification: AGW

Value: 400 ml/m<sup>3</sup> (ppm), 1500 mg/m<sup>3</sup>

Peak limitation: 2 (I)

Toxic to reproduction: Y - a risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Remark: DFG

**DNEL/DMEL-Values**

No data available.

**PNEC-Values**

No data available.

**8.2 Occupational exposure controls**

Technical measures and the application of suitable working methods have precedence before the application of personal protective equipment. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Suitable judgement methods of the examination of the effectiveness of the grievied preventive measures enclose measuring-technical and non-technical inquiry methods like they in the technical rules for danger materials (TRGS) 402.

**Personal protective equipment**

Do not eat or drink during work – No smoking. Keep away from foodstuffs and beverages. Wash hands before breaks and after work. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately.

**Respiratory protection**

Take breathing protection measures (see also instruct to avoid accidents). Breathing protection equipment required in inadequately ventilated places and during spraying.

Respiratory filter (gas): A1 (brown) until 1000 ml/m<sup>3</sup> (ppm)

A2 (brown) until 5000 ml/m<sup>3</sup> (ppm)

A3 (brown) until 10000 ml/m<sup>3</sup> (ppm)

Details are to be inferred "from the rules for the use of respiratory protective devices" (BGR 190 (German regulation)).



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 7 of 13**

**Skin protection**

Avoid contact with skin. Use protective gloves (EN 374). Solvent-resistant protective gloves must be worn. The glove material must be sufficiently impermeable and resistant to the substance. Check the tightness before wear. Gloves should be well cleaned before being removed, then stored in a well ventilated location. Textile or leather gloves are completely unsuitable. Following materials are unsuitable for protective gloves because of degradation, severe swelling or low permeation time: Natural rubber/Natural latex – NR, Polychloroprene – CR, Fluoro carbon rubber – FKM, Polyvinyl chloride – PVC. Pay attention to skin care.

The following materials are suitable for protective gloves

Inherent protection

Polyvinyl alcohol – PVA (- mm): Permeation time  $\geq 8$  hour

Butyl/Viton (0,7 mm): Permeation time  $\geq 8$  hour

Splash guard

Butyl rubber - Butyl (0,5 mm): Permeation time 1 hour

Nitrile rubber/Nitrile latex – NBR (0,38 mm): Permeation time 18 minutes

The times listed are suggested by measurements taken at 22 °C and constant contact. Temperatures raised by warmed substances, body heat, etc. and a weakening of the effective layer thickness caused by expansion can lead to a significantly shorter breakthrough time. In case of doubt contact the gloves' manufacturer. A 1.5-times increase / decrease in the layer thickness doubles / halves the breakthrough time. This data only applies to the pure substance. Transferred to mixtures of substances, these figures should only be taken as an aid to orientation.

**Eye protection**

Avoid contact with eyes. Use safety glasses according to 166:2001.

**Body protection**

Personnel should wear antistatic clothing's made of natural fibre or of high temperature resistant synthetic fibre. All parts of the body should be washed after contact. Light protective clothing.

**Limitation and supervision of the environmental exposition**

See section 6 and 7.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 General information**

**Form:** fluid  
**Colour:** colourless  
**Odour:** fruity

**9.2 Relevant safety data**

**Flashpoint:** - 4 °C                      DIN EN 22719  
**Viscosity:** > 30 s                      ISO 2431  
**Density: (20 °C)** approx. 0,9 g/cm<sup>3</sup>                      DIN 53217



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 8 of 13**

**Explosive limits:**

Lower / Upper: 2,1 Vol.-% / 11,5 Vol.-%

**Ignition temperature:** not determined

**Vapour pressure:** not determined (20 °C)

**pH-value:** not applicable

**Solubility in water:** insoluble

**9.3 Additional information**

No other physical-chemical data available.

---

**10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. See section 7.

**10.2 Chemical stability**

If handled properly then product has chemical stability.

**10.3 Possible dangerous reactions**

None, if handled according to order. Further instructions see section 10.1 and 10.2.

**10.4 Conditions to avoid**

Only use the material in places where open light, fire and other flammable sources can be kept away.

**10.5 Incompatible materials**

See section 10.1.

**10.6 Hazardous decomposition products**

When product exposed to high temperatures, it may produce hazardous decomposition products such as carbon monoxide and carbon dioxide, smoke and other hazardous components.

---

**11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity**

**Ethyl acetate; CAS No. 141-78-6**

LD<sub>50, oral, rat</sub> = 5620 mg/kg (Reference: Yakkyoku. Pharmacy. Vol. 32, Pg. 1241, 1981.)

LD<sub>50, dermal, rabbit</sub> = 18000 mg/kg (Reference: Union Carbide Data Sheet. Vol. 10/4/1968.)

Remark: Substance/product listed in Regulation (EC) 1272/2008.





**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 9 of 13**

**Primary irritant effect  
after inhalation**

Vapours may cause drowsiness and dizziness. Exposure to component solvents vapour concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

**on the skin  
on the eyes**

Repeated exposure may cause skin dryness or cracking.

Irritant to eyes. Irritative effects, such as redness, lacrimation, blepharospasm, corneal clouding.

**after ingestion**

At higher concentrations of ethyl acetate has a narcotic effect. At a low dose anti-spasmodic and for deepening the breathing acts. Symptoms: paralysis of the central nervous system and reflex loss, muscle relaxation, loss of consciousness, switch off vital regulatory mechanisms, central respiratory paralysis. In some cases, an allergic reaction of the organism possible.

**Sensitization  
Chronic**

There are no data available on the preparation itself.

There are no data available on the preparation itself.

**11.2 Additional toxicological information**

The product is classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

---

**12. ECOLOGICAL INFORMATION**

**12.1 Ecotoxicity**

**Ethyl acetate; CAS No. 141-78-6**

LC<sub>50, fish, 96h</sub> = 328 mg/l

(Reference: Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (*Pimephales promelas*), Vol. 1. Center for Lake Superior Environmental Stud., Univ. of Wisconsin-Superior, Superior, WI :414; Douglas, M.T., D.O. Chanter, I.B. Pell, and G.M. Burney 1986. A Proposal for the Reduction of Animal Numbers Required for the Acute Toxicity to Fish Test (LC<sub>50</sub> Determination). *Aquat.Toxicol.* 8(4):243-249.)

LC<sub>50, crustaceans, 48h</sub> = 679 mg/l

(Reference: Canton, J.H., and D.M.M. Adema 1978. Reproducibility of Short-Term and Reproduction Toxicity Experiments with *Daphnia magna* and Comparison of the Sensitivity of *Daphnia magna* with *Daphnia pulex* and *Daphnia cucullata* in Short-Term Experiments. *Hydrobiologia* 59(2):135-140 (Used Reference 2018).)

EC<sub>50, algae, 96h</sub> = 2500 mg/l

(Reference: Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. *Natl.Tech.Inf.Serv.*, Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386))

Remark:

-



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 10 of 13**

**12.2 Persistence/degradability**

There are no data available.

**12.3 Bioaccumulative potential**

There are no data available.

**12.4 Mobility**

There are no data available.

**12.5 Results of PBT and vPvP assessment**

There are no data available.

**12.6 Other adverse effects**

There are no data available.

**12.7 Further ecological information**

Do not discharge into the drains/surface waters/groundwater.

Water hazard class: WGK 1 slightly hazardous to water

---

**13. DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

Send to a hazardous waste incinerator facility under observation of official regulations. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**Recommendation**

Disposal must be made according to official regulations.

**13.2 European waste code number in accordance with AAV**

EWC No.: 08 01 04 waste paint and varnish containing organic solvents or other dangerous substances

EWC No.: 20 01 27 paint, inks, adhesives and resins containing dangerous substances

**13.3 Packaging**

**Contaminated packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing, may be taken for reuse. Packaging that cannot be cleaned should be disposed in the same manner as the medium.

EWC No. 15 01 10 packaging containing residues of or contaminated by dangerous substances

**Non-contaminated packages**

EWC No.: 15 01 02 plastic packaging

EWC No.: 15 01 07 glass packaging



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 11 of 13**

**14. TRANSPORT INFORMATION**

**14.1 Land transport ADR/RID and GVS/GGVE**



Class: 3 Flammable liquids  
Kemler-Code: 33  
UN No.: 1263  
Packaging group: II  
Label: 3  
Special marking: -  
Proper shipping name: 1263 – Paint (Contains Ethyl acetate.)  
Classification-Code: F1  
Limit: 1 L  
Tunnel restriction code: 2 (D/E)

**14.2 Maritime transport IMDG/GGVSea**



Class: 3  
UN No.: 1263  
Label: 3  
Packaging group: II  
EmS-No.: F-E, S-E  
Marine pollutant: -  
Proper shipping name: 1263 – Paint (Contains Ethyl acetate.)

**14.3 Air transport ICAO-TI and IATA-DGR**



ICAO/IATA Class: 3  
UN no.: 1263  
Label: 3  
Packaging group: II  
Proper shipping name: 1263 – Paint (Contains Ethyl acetate.)

**14.3 Remarks**

Product contains environmentally hazardous substances: -



**Material Safety Data Sheet according to Regulation (EC) No. 1907/2006  
(revised by Regulation (EC) No. 453/2010)**

**SOLO GOYA Clear lacquer**

**Page 12 of 13**

---

**15. REGULATORY INFORMATION**

**15.1 European Regulation**

**Chemical Safety Assessment:** For this substance a chemical safety assessment is not required.

**15.2 National Regulations**

Statutory order on hazardous incidents (StörfallV): Annex I, Nr. 6, 9b

Regulation on inflammable liquids: VbF-Class: All

Emission control act ("TA-Luft"): 3.1.7 Class III

Water hazard class: WGK 1 slightly hazardous to water (according VwVwS)

**15.3 Additional information**

The product is classified according to the EEC directives and the Ordinance on Hazardous Materials (GefStoffV).

If bottle ≤ 125 ml then the following H- and P-phrases are not necessary: H225, H319, P210, P280, P305+351+338, P337+313, P370+378.

Please check local regulations.

Volatile organic compounds (Swiss): 72,7 %; 32,7 g/50ml; 0,653 kg/l

The advertised use (section 1) is not subject of the Directive 2004/42/EC.

---

**16. OTHER INFORMATION**

**16.1 Changes compared with the last version**

The last version was all changed and revised completely. Alterations to the previous edition are marked in the right-hand margin.

**16.2 Literature reference and data source**

Regulation (EC) 1999/45, last changed by Regulation (EC) 1907/2006

Regulation (EC) 67/548, last changed by Regulation (EC) 2009/2

REACH Regulation (EC) 1907/2006, last changed by Regulation (EC) 453/2010

Regulation (EC) 1272/2008, last changed by Regulation (EC) 790/2009

**Internet**

<http://www.baua.de>

<http://www.arbeitssicherheit.de>

<http://www.gischem.de>

**16.3 Full text of H- and R-phrases appearing in section 2 and 3:  
According to Regulation (EC) 1272/2008**

Flam. Liq. 2 H225                      Highly flammable liquid and vapour.

Eye Irrit. 2 H319                      Causes serious eye irritation.

STOT SE 3 H336                      May cause drowsiness or dizziness.

\* minimum classification

**EUH – statements**

EUH066      Repeated exposure may cause skin dryness or cracking.



## Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (revised by Regulation (EC) No. 453/2010)

SOLO GOYA Clear lacquer

Page 13 of 13

**Methods according to article 9 of the order (EC) No. 1272/2008 for the assessment of the information for the purpose of the classification were used:**

Classification according to Regulation 1272/2008.

### 16.4 Abbreviations and acronyms

<b>ADR:</b>	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
<b>BImSchV:</b>	Order for the realisation of the Federal Immission Protection Law
<b>CAS:</b>	Chemical Abstracts Service
<b>DIN:</b>	Norm of the German institute of standardization
<b>EC:</b>	Effective concentration
<b>EC50:</b>	Effective concentration, 50 percent
<b>EG:</b>	European Community
<b>EINECS:</b>	European Inventory of Existing Commercial Chemical Substances
<b>EN:</b>	European Standard
<b>GefStoffV:</b>	Ordinance on Hazardous Substances, Germany
<b>GHS:</b>	Globally Harmonized System of Classification and Labelling of Chemicals
<b>IATA:</b>	International Air Transport Association
<b>IMDG:</b>	International Maritime Code for Dangerous Goods
<b>LC50:</b>	Lethal concentration, 50 percent
<b>LD50:</b>	Lethal dose, 50 percent
<b>Log K<sub>ow</sub>:</b>	n-octanol-water partition coefficient
<b>OECD:</b>	Organisation for Economic Co-operation and Development
<b>PBT:</b>	Persistent, bioaccumulateable, toxically
<b>RID:</b>	Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
<b>TRGS:</b>	Technical rules for danger materials
<b>UN:</b>	United Nations (Vereinte Nationen)
<b>VOC:</b>	Volatile Organic Compounds
<b>vPvB:</b>	very much persistent and very bioaccumulateable
<b>VwVwS:</b>	Administrative regulation of hazardous to waters materials
<b>WGK:</b>	Water hazardous class

### 16.5 Department issuing safety data sheet

Laboratory, Mrs. Dipl.-Ing. Treiber, [b.treiber@c-kreul.de](mailto:b.treiber@c-kreul.de).

### 16.6 Additional information

The data is based on our present knowledge. The data correspond to the national and EEC legislation. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

It is not permitted to use the product for any other application mentioned in chapter 1 except with a written permission. The user is responsible for the compliance with all valid legal regulation.

This safety data sheet is only valid for SOLO GOYA Clear lacquer. It's not valid for other products placed in the according sales displays or sets.