

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.05.2022

Version number 1.2 (replaces version 1.1)

Revision: 19.05.2022

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:**
KREUL Permanent Marker medium Black
KREUL Permanent Marker edge Black
KREUL Permanent Marker fine Black
KREUL Permanent Marker XXL Black
(Safety data sheet for the included ink.)
- **Article number:** 47611, 47811, 47711, 48011
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 No further relevant information available.
- **Application of the substance / the mixture**
 Paint
 For artists and hobby user.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 C. KREUL GmbH & Co. KG
 Carl-Kreul-Straße 2
 D-91352 HALLERNDORF
 DEUTSCHLAND
 Tel. + 49 (0)9545 / 925 - 0
 Fax + 49 (0)9545 / 925 - 511
 E-Mail: info@c-kreul.de
- **Further information obtainable from:**
 Product Safety Department:
 Treiber, b.treiber@c-kreul.de
- **1.4 Emergency telephone number:** +44 (0)171 635 91 91

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

- **2.2 Label elements**
 EC Regulation 1907/2006 (GB REACH) differentiates between substances, mixtures and articles. In accordance with the definition of articles in GB REACH, the European Writing Instrument Manufacturer's Association (EWIMA) considers writing instruments, marker pens etc. to be articles. However, no safety data sheets are provided for articles. In contrast, safety data sheets are mandatory for substances and mixtures. For this reason, the information in the safety data sheet provided always refers to the basic ink and not to the product as a whole.
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02

- **Signal word** Danger
- **Hazard statements**
 H225 Highly flammable liquid and vapour.
- **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P271	Use only outdoors or in a well-ventilated area.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.05.2022

Version number 1.2 (replaces version 1.1)

Revision: 19.05.2022

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX	ethanol ⚠ Flam. Liq. 2, H225	50-<100%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-<10%
	Methine dye preparation ⚠ Aquatic Chronic 2, H411; ⚠ Eye Irrit. 2, H319	<2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Wash with water and acidic soap.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Remove contact lenses.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
If symptoms persist consult doctor.
Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.05.2022

Version number 1.2 (replaces version 1.1)

Revision: 19.05.2022

See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
Fumes can combine with air to form an explosive mixture.
Protect from heat.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Protect from frost.

7.3 Specific end use(s) See chapter 1.2.

8 Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
Sk

DNELs

64-17-5 ethanol

Oral	long-term exposure-systemic effects	87 mg/kg (general population)
Dermal	long-term exposure-systemic effects	206 mg/kg bw/d (general population) 343 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	114 mg/m ³ (general population) 950 mg/m ³ (worker)

107-98-2 1-methoxy-2-propanol

Oral	long-term exposure-systemic effects	33 mg/kg (general population)
Dermal	long-term exposure-systemic effects	183 mg/kg bw/d (general population) 78 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	43.9 mg/m ³ (general population) 369 mg/m ³ (worker)

PNECs

64-17-5 ethanol

water	2.75 mg/l
freshwater	0.96 mg/l
marine water	0.79 mg/l
sewage treatment plant (STP)	580 mg/l
freshwater sediment	3.6 mg/kg
soil	0.63 mg/kg

107-98-2 1-methoxy-2-propanol

water	100 mg/l
freshwater	10 mg/l
marine water	1 mg/l
sewage treatment plant (STP)	100 mg/l
freshwater sediment	52.3 mg/kg
marine sediment	5.2 mg/kg
soil	4.59 mg/kg

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.05.2022

Version number 1.2 (replaces version 1.1)

Revision: 19.05.2022

(Contd. of page 3)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Do not eat, drink, smoke or sniff while working.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact gloves made of the following materials are suitable:**
Butyl rubber, BR
Recommended thickness of the material: ≥ 0.4 mm
Value for the permeation: Level ≤ 4 h
- **Eye/face protection**



Tightly sealed goggles

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

- | | |
|---|------------------------------------|
| · Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | 78 °C |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | 3.5 Vol % |
| · Upper: | 15 Vol % |
| · Flash point: | 13 °C |
| · Ignition temperature: | 425 °C |
| · Decomposition temperature: | Not determined. |
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic: | Not determined. |
| · Solubility | |
| · water: | Not determined. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C: | 59 hPa |
| · Density and/or relative density | |
| · Density: | Not determined. |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

· 9.2 Other information

- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.05.2022

Version number 1.2 (replaces version 1.1)

Revision: 19.05.2022

(Contd. of page 4)

- **Change in condition**
- **Evaporation rate** Not determined.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids**
Highly flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

64-17-5 ethanol

Oral	LD50	10,470 mg/kg (rat) (OECD 403)
Dermal	LD50	>2,000 mg/kg (rat)
		12,800 mg/kg (rabbit)
Inhalative	LC50/4h	124.7 mg/m ³ (rat) (OECD 403)

107-98-2 1-methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat) (EU B.1, ECHA)
Dermal	LD50	13,000 mg/kg (rab)
		>2,000 mg/kg (rat) (EU B.3, ECHA)
Inhalative	LC50/4h	30.04 mg/m ³ (rat) (ECHA)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

GB
(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.05.2022

Version number 1.2 (replaces version 1.1)

Revision: 19.05.2022

(Contd. of page 5)

12 Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

64-17-5 ethanol

LC50/96h	14,200 mg/l (pimephales promelas) (US EPA method E03-0)
	13,000 mg/l (oncorhynchus mykiss)
LC50/48h	5,012 mg/l (ceriodaphnia dubia) (ASTM E729-80)
	12,340 mg/l (daphnia magna)
EC50/48h	12,900 mg/l (algae)
	>10,000 mg/l (ceriodaphnia dubia) (DIN 38412 Teil 11)
	9,950 mg/l (crustaceans)
EC50/96h	12,900 mg/l (pimephales promelas) (US EPA method E03-0)
NOEC	2 mg/l /10d (ceriodaphnia dubia) (ECHA)
	250 mg/l /120h (danio rerio) (OECD 212)
ErC50	275 mg/l /72h (algae) (OECD 201)
ErCx 10%	11.5 mg/l /3d (algae) (OECD 201)
LC50	1,806 mg/l /10d (ceriodaphnia dubia) (ECHA)
	454 mg/l /9d (daphnia magna) (ECHA)

107-98-2 1-methoxy-2-propanol

LC50/96h	1,000 mg/l (oncorhynchus mykiss) (OECD 203)
LC50/48h	21,100–25,900 mg/l (daphnia magna) (ESR-ES-15)
ErC50	>1,000 mg/l /7d (pseudokirchneriella subcapitata) (ECHA)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Smaller quantities can be disposed of with household waste.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· 14.1 UN number or ID number

· **ADR, IMDG, IATA** UN1263

· 14.2 UN proper shipping name

· **ADR, IMDG, IATA** 1263 PAINT
PAINT

· 14.3 Transport hazard class(es)

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· 14.4 Packing group

· **ADR, IMDG, IATA** II

· 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Hazard identification number (Kemler code):

33

· EMS Number:

F-E,S-E

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.05.2022

Version number 1.2 (replaces version 1.1)

Revision: 19.05.2022

(Contd. of page 6)

· Stowage Category	B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	

· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product Safety Department

· **Contact:** B. Treiber, b.treiber@c-kreul.de

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (GB REACH)

PNEC: Predicted No-Effect Concentration (GB REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**

GB