

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2019

Version number 1.0

Revision: 10.01.2019

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** KREUL Acrylic matt varnish synthetic resin based 50 ml, 250 ml
- **Article number:** 79409, 79410
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Lacquer
For artists and hobby user.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
C. KREUL GmbH & Co. KG
Carl-Kreul-Straße 2
D-91352 HALLERNDORF
DEUTSCHLAND
Tel. + 49 (0)9545 / 925 - 0
Fax + 49 (0)9545 / 925 - 511
E-Mail: info@c-kreul.de
- **Further information obtainable from:**
Product Safety Department:
Treiber, b.treiber@c-kreul.de
- **1.4 Emergency telephone number:** +44 (0)171 635 91 91

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Naphtha (petroleum), hydrotreated heavy
- **Hazard statements**
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2019

Version number 1.0

Revision: 10.01.2019

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P271 Use only outdoors or in a well-ventilated area.
 P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH208 Contains isobutyl methacrylate. May produce an allergic reaction.

· **2.3 Other hazards**

Vapours may form explosive mixtures with air. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment). Take precautionary measures against static discharges.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

3 Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33-XXXX	Naphtha (petroleum), hydrotreated heavy ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	25-<50%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-219455851-35-XXXX	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; STOT SE 3, H335-H336	10-<20%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-<5%
CAS: 97-86-9 EINECS: 202-613-0 Index number: 607-113-00-X Reg.nr.: 01-2119488331-38-XXXX	isobutyl methacrylate ⚠ Flam. Liq. 3, H226; ⚠ Aquatic Acute 1, H400; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **4.1 Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.
 In case of unconsciousness place patient stably in side position for transportation.
 Seek immediate medical advice.

· **After skin contact:**

Wash with water and acidic soap.
 If skin irritation continues, consult a doctor.

· **After eye contact:**

Remove contact lenses.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.
 Administer medicinal carbon.
 A person vomiting while laying on their back should be turned onto their side.
 Seek immediate medical advice.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2019

Version number 1.0

Revision: 10.01.2019

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
If swallowed or in case of vomiting, danger of entering the lungs.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Use respiratory protective device against the effects of fumes/dust/aerosol.
Keep away from ignition sources.
Wear protective equipment. Keep unprotected persons away.
Mount respiratory protective device.
- **6.2 Environmental precautions:**
Keep contaminated washing water and dispose of appropriately.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Take note of emission threshold.
Prevent formation of aerosols.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
No special requirements.
Store in a cool location.
- **Information about storage in one common storage facility:**
Do not store together with oxidising and acidic materials.
Do not store together with alkalis (caustic solutions).
- **Further information about storage conditions:**
Store receptacle in a well ventilated area.
Keep container tightly sealed.
- **Storage class:** 2B

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2019

Version number 1.0

Revision: 10.01.2019

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

· DNELs

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	long-term exposure-systemic effects	300 mg/kg (general population)
Dermal	long-term exposure-systemic effects	300 mg/kg bw/d (general population) 300 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	900 mg/m ³ (general population) 1,500 mg/m ³ (worker)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	long-term exposure-systemic effects	11 mg/kg (general population)
Dermal	long-term exposure-systemic effects	11 mg/kg bw/d (general population) 25 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	32 mg/m ³ (general population) 150 mg/m ³ (worker)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	long-term exposure-systemic effects	1.67 mg/kg (general population)
Dermal	long-term exposure-systemic effects	54.8 mg/kg bw/d (general population) 153.5 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	33 mg/m ³ (general population) 275 mg/m ³ (worker)

· PNECs

108-65-6 2-methoxy-1-methylethyl acetate

freshwater	0.635 mg/l
marine water	0.0635 mg/l
sewage treatment plant (STP)	100 mg/l
freshwater sediment	3.29 mg/kg
soil	0.29 mg/kg

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device when high concentrations are present.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2019

Version number 1.0

Revision: 10.01.2019

(Contd. of page 4)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level ≤ 8 h

- **As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.12 mm

Value for the permeation: Level $\leq 2-4$ h

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

- **Flash point:** >23 °C

- **Flammability (solid, gas):** Not applicable.

- **Ignition temperature:** <237 °C

- **Decomposition temperature:** Not determined.

- **Auto-ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower:	1.5 Vol %
Upper:	10.8 Vol %

- **Vapour pressure at 20 °C:** 2.6 hPa

- **Density at 20 °C:** 0.88 g/cm³

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

- **Partition coefficient: n-octanol/water:** Not determined.

- **Viscosity:**

Dynamic:	Not determined.
Kinematic at 40 °C:	>20.5 mm ² /s

- **Solvent content:**

Organic solvents:	64 %
VOC (EC)	64 %

- **Solids content:** 35.9 %

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2019

Version number 1.0

Revision: 10.01.2019

(Contd. of page 5)

9.2 Other information

No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Keep away from oxidizing agents, strong alkaline and acidic materials.
- **10.6 Hazardous decomposition products:**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:****64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4h	>10.2 mg/m ³ (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rab)
Inhalative	LC50/4h	35.7 mg/m ³ (rat)

97-86-9 isobutyl methacrylate

Oral	LD50	11,990 mg/kg (mouse)
------	------	----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information· **12.1 Toxicity**· **Aquatic toxicity:****64742-95-6 Solvent naphtha (petroleum), light arom.**

LC50/96h	>1,000 mg/l (oncorhynchus mykiss)
EC50/48h	>1,000 mg/l (daphnia magna)

108-65-6 2-methoxy-1-methylethyl acetate

LC50/96h	134 mg/l (oncorhynchus mykiss)
EC50/48h	>500 mg/l (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2019

Version number 1.0

Revision: 10.01.2019

(Contd. of page 6)

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations


- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances
15 01 07	glass packaging
HP 3	Flammable
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · 14.1 UN-Number
· ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name
· ADR
· IMDG, IATA | 1263 PAINT
PAINT |
| · 14.3 Transport hazard class(es)
· ADR, IMDG, IATA | |
|  | |
| · Class
· Label | 3 Flammable liquids.
3 |
| · 14.4 Packing group
· ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user
· Danger code (Kemler):
· EMS Number:
· Stowage Category | Warning: Flammable liquids.
30
F-E, <u>S-E</u>
A |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR
· Limited quantities (LQ) | 5L |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.01.2019

Version number 1.0

Revision: 10.01.2019

(Contd. of page 7)

· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product Safety Department

· **Contact:** B. Treiber, b.treiber@c-kreul.de

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3