

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2019

Version number 1.1

Revision: 11.09.2019

**1 Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** KREUL Matt lacquer Spray 150 ml, 400 ml
- **Article number:** 821150, 821400
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Lacquer  
For artists and hobby user.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
C. KREUL GmbH & Co. KG  
Carl-Kreul-Straße 2  
D-91352 HALLERNDORF  
DEUTSCHLAND  
Tel. + 49 (0)9545 / 925 - 0  
Fax + 49 (0)9545 / 925 - 511  
E-Mail: info@c-kreul.de
- **Further information obtainable from:**  
Product Safety Department:  
Treiber, b.treiber@c-kreul.de
- **1.4 Emergency telephone number:** +44 (0)171 635 91 91

**2 Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1      H222-H229    Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS05 corrosion

Eye Dam. 1      H318      Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2    H411      Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2      H315      Causes skin irritation.  
STOT SE 3      H335-H336    May cause respiratory irritation. May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS05



GHS07



GHS09

- **Signal word** Danger

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 11.09.2019

Version number 1.1

Revision: 11.09.2019

(Contd. of page 1)

### · Hazard-determining components of labelling:

butan-1-ol  
hydrocarbons, C7-C9  
hydrocarbons, C6-C7

### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### · Additional information:

EUH208 Contains n-butyl methacrylate. May produce an allergic reaction.

### · 2.3 Other hazards

### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.  
· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

### · 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

### · Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-XXXX	dimethyl ether ⚠ Flam. Gas 1, H220; Press. Gas C, H280	25- $<$ 50%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-XXXX	butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	20- $<$ 25%
EC number: 920-750-0 Reg.nr.: 01-2119473851-33-XXXX	hydrocarbons, C7-C9 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	5- $<$ 10%
CAS: 64742-48-9 EINECS: 265-150-3 Index number: 649-327-00-6 Reg.nr.: 01-2119486659-16-XXXX	Naphtha (petroleum), hydrotreated heavy ⚠ Asp. Tox. 1, H304	5- $<$ 10%
EC number: 926-605-8 Reg.nr.: 01-2119473851-33-XXXX	hydrocarbons, C6-C7 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	2.5- $<$ 5%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1	cyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	2.5- $<$ 5%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	$<$ 0.5%
CAS: 79-41-4 EINECS: 201-204-4 Index number: 607-088-00-5 Reg.nr.: 01-2119463884-26-XXXX	methacrylic acid ⚠ Acute Tox. 3, H311; ⚠ Skin Corr. 1A, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335	$<$ 0.5%
CAS: 97-88-1 EINECS: 202-615-1 Index number: 607-033-00-5 Reg.nr.: 01-2119486394-28-XXXX	n-butyl methacrylate ⚠ Flam. Liq. 3, H226; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	$<$ 0.5%

### · Additional information:

Benzene (EINECS 200-753-7)  $<$ 0.1%. (Note P Annex VI to Directive (EC) No 1272/2008)  
For the wording of the listed hazard phrases refer to section 16.

## 4 First aid measures

### · 4.1 Description of first aid measures

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 11.09.2019

Version number 1.1

Revision: 11.09.2019

(Contd. of page 2)

- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.  
Remove contact lenses.
- **After swallowing:**  
Drink plenty of water and provide fresh air. Call for a doctor immediately.  
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Use neutralising agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2B
- **7.3 Specific end use(s)** See chapter 1.2.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

#### 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

##### 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm
-----	---

##### 71-36-3 butan-1-ol

WEL	Short-term value: 154 mg/m <sup>3</sup> , 50 ppm Sk
-----	--

(Contd. on page 4)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.09.2019

Version number 1.1

Revision: 11.09.2019

(Contd. of page 3)

**110-82-7 cyclohexane**

WEL	Short-term value: 1050 mg/m <sup>3</sup> , 300 ppm
	Long-term value: 350 mg/m <sup>3</sup> , 100 ppm

**110-54-3 n-hexane**

WEL	Long-term value: 72 mg/m <sup>3</sup> , 20 ppm
-----	--

**79-41-4 methacrylic acid**

WEL	Short-term value: 143 mg/m <sup>3</sup> , 40 ppm
	Long-term value: 72 mg/m <sup>3</sup> , 20 ppm

**· DNELs****64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral	long-term exposure-systemic effects	300 mg/kg (general population)
Dermal	long-term exposure-systemic effects	300 mg/kg bw/d (general population) 300 mg/kg bw/d (worker)
Inhalative	long-term exposure-systemic effects	900 mg/m <sup>3</sup> (general population) 1,500 mg/m <sup>3</sup> (worker)

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

**· Respiratory protection:**

Filter AX

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· For the permanent contact gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.4$  mmValue for the permeation: Level  $\leq 8$ h**· As protection from splashes gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.4$  mmValue for the permeation: Level  $\leq 8$ h**· Eye protection:**

Tightly sealed goggles

## 9 Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	According to product specification
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

(Contd. on page 5)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.09.2019

Version number 1.1

Revision: 11.09.2019

(Contd. of page 4)

· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	Not applicable, as aerosol.
· <b>Flash point:</b>	Not applicable, as aerosol.
· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Ignition temperature:</b>	240 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Not determined.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.5 Vol %
<b>Upper:</b>	26.2 Vol %
· <b>Vapour pressure at 20 °C:</b>	4,000 hPa
· <b>Density at 20 °C:</b>	0.74 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	~80 %
<b>VOC (EC)</b>	78.09 %
<b>Solids content:</b>	18.0 %
· <b>9.2 Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### LD/LC50 values relevant for classification:

#### 115-10-6 dimethyl ether

Inhalative	LC50/4h	308 mg/m <sup>3</sup> (rat)
------------	---------	-----------------------------

#### 71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h	8,000 mg/m <sup>3</sup> (rat)

#### hydrocarbons, C7-C9

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,800 mg/kg (rat)
Inhalative	LC50/4h	22 mg/m <sup>3</sup> (rat)

#### 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4h	>4,951 mg/m <sup>3</sup> (rat)

#### 110-82-7 cyclohexane

Oral	LD50	12,705 mg/kg (rat)
------	------	--------------------

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 11.09.2019

Version number 1.1

Revision: 11.09.2019

(Contd. of page 5)

**110-54-3 n-hexane**

Oral	LD50	25,000 mg/kg (rat)
Inhalative	LC50/4h	169,000 mg/m <sup>3</sup> (rat)

**79-41-4 methacrylic acid**

Oral	LD50	1,332 mg/kg (mouse)
Dermal	LD50	500 mg/kg (rabbit)
Inhalative	LC50/4h	11 mg/m <sup>3</sup> (ATE)

**97-88-1 n-butyl methacrylate**

Oral	LD50	22,600 mg/kg (rat)
Dermal	LD50	11,300 mg/kg (rabbit)
Inhalative	LC50/4h	4,910 mg/m <sup>3</sup> (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**12 Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****115-10-6 dimethyl ether**

LC50/96h	>4,000 mg/l (fish)
LC50/48h	>4,000 mg/l (daphnia magna)
EC50/96h	155 mg/l (algae)

**71-36-3 butan-1-ol**

LC50/96h	1,376 mg/l (fish)
----------	-------------------

**hydrocarbons, C7-C9**

LC50/96h	>13.4 mg/l (oncorhynchus mykiss)
LC50/48h	3 mg/l (daphnia magna)
LC50/72h	20 mg/l (pseudokirchneriella subcapitata)

**110-54-3 n-hexane**

LC50/96h	57.8 mg/l (fish)
----------	------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.**13 Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.· **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.09.2019






Version number 1.1

Revision: 11.09.2019

	(Contd. of page 6)
15 01 10*	packaging containing residues of or contaminated by hazardous substances
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

<ul style="list-style-type: none"> <li>· 14.1 UN-Number</li> <li>· ADR, IMDG, IATA</li> </ul>	UN1950
<ul style="list-style-type: none"> <li>· 14.2 UN proper shipping name</li> <li>· ADR</li> <li>· IMDG</li> <li>· IATA</li> </ul>	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (hydrocarbons, C7-C9, hydrocarbons, C6-C7), MARINE POLLUTANT AEROSOLS, flammable
<ul style="list-style-type: none"> <li>· 14.3 Transport hazard class(es)</li> <li>· ADR</li> </ul>	<div style="display: flex; align-items: center; gap: 10px;">   </div>
<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	2.1 2.1
<ul style="list-style-type: none"> <li>· IMDG</li> </ul>	<div style="display: flex; align-items: center; gap: 10px;">   </div>
<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	2.1 2.1
<ul style="list-style-type: none"> <li>· IATA</li> </ul>	<div style="display: flex; align-items: center; gap: 10px;">  </div>
<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	2.1 2.1
<ul style="list-style-type: none"> <li>· 14.4 Packing group</li> <li>· ADR, IMDG, IATA</li> </ul>	not regulated
<ul style="list-style-type: none"> <li>· 14.5 Environmental hazards:</li> <li>· Marine pollutant:</li> <li>· Special marking (ADR):</li> </ul>	Product contains environmentally hazardous substances: hydrocarbons, C7-C9 Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> <li>· 14.6 Special precautions for user</li> <li>· Danger code (Kemler):</li> <li>· EMS Number:</li> <li>· Stowage Code</li> <li>· Segregation Code</li> </ul>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW2 Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
<ul style="list-style-type: none"> <li>· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· Transport/Additional information:</li> </ul>	<ul style="list-style-type: none"> <li>· ADR</li> <li>· Limited quantities (LQ)</li> </ul>
<ul style="list-style-type: none"> <li>· Limited quantities (LQ)</li> </ul>	1L

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 11.09.2019

Version number 1.1

Revision: 11.09.2019

(Contd. of page 7)

· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
<hr style="border-top: 1px dashed black;"/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

### 15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
P3a FLAMMABLE AEROSOLS  
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 57
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product Safety Department

· **Contact:** B. Treiber, b.treiber@c-kreul.de

#### · **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas C: Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 3: Acute toxicity – Category 3
- Skin Corr. 1A: Skin corrosion/irritation – Category 1A
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.09.2019

Version number 1.1

Revision: 11.09.2019

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
· \* **Data compared to the previous version altered.**

(Contd. of page 8)

GB